



UF15P(C) Series



Thermal Protection

Terminal or Lead Wire Type



ZOOM



Spec.	Rated Voltage	Frequency	Input Power	Rated Current	Locked Current	Speed	Maximum Air Flow	Maximum Air Flow	Maximum Pressure	Maximum Pressure	Noise	Weight
Model	V	Hz	W	A	A	RPM	m ³ /min.	CFM	mmH ₂ O	InchH ₂ O	dB	kg
UF15PC10-H	100V	50	30	0.33	0.50	2850	5.8	205	16	0.63	53	0.9
		60	30	0.29	0.52	3400	6.4	226	20	0.79	58	
UF15PC11-H	115V	50	31	0.26	0.41	2850	5.8	205	16	0.63	53	0.9
		60	31	0.25	0.43	3400	6.4	226	20	0.79	58	
UF15PC20-H	200V	50	29	0.15	0.23	2850	5.8	205	16	0.63	53	0.9
		60	29	0.14	0.25	3400	6.4	226	20	0.79	58	
UF15PC23-H	230V	50	29	0.12	0.19	2850	5.8	205	16	0.63	53	0.9
		60	29	0.12	0.19	3400	6.4	226	20	0.79	58	
UF15PC11-L	115V	50	31	0.17	0.21	1400	2.5	88	3.8	0.15	31	0.9
		60	31	0.15	0.20	1700	3.0	106	5.5	0.22	37	
UF15PC23-L	230V	50	29	0.08	0.09	1400	2.5	88	3.8	0.15	31	0.9
		60	29	0.07	0.09	1700	3.0	106	5.5	0.22	37	