

SPECIFICATIONS

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

MODEL	UF-92AM11BTHF
ITEM	
RATED VOLTAGE	AC115V
VOLTAGE RANGE	AC103-126V
SPEED(RPM)	50Hz 2700 RPM±10% 60Hz 3200 RPM±10%
RATED CURRENT	50Hz 0.14 A±10% 60Hz 0.12 A±10%
RATED INPUT	50Hz 12 W±10% 60Hz 11 W±10%
LOCKED CURRENT	50Hz 0.19 A±10% 60Hz 0.17 A±10%
MAX. AIR VOLUME	50Hz 44±10% CFM 60Hz 51±10%1 CFM
MAX. STATIC PRESSURE	50Hz 0.24±10%4 inH2O 60Hz 0.30±10% inH2O
OPERATING TEMP.	-40°C~+90°C
STORAGE TEMP.	-40°C~+90°C
ROTATING DIRECTION	ANTI-CLOCKWISE DIRECTION
BLOWING DIRECTION	EXHAUST OVER STRUTS
INSULATION RESISTANCE	DC 500 V 100MΩ
DIELECTRIC STRENGTH	AC 1500V / 1MIN.
NOISE	50Hz 37dB 60Hz 42dB
SAFETY PROTECTION	IMPEDANCE PROTECTION
INSULATION GRADE	CLASS F
BEARING	BALL BEARING
LIFE EXPECTANCY	OVER 40000 HOURS (40°C)
FRAME MATERIAL	ALUMINUM (ADC-12)
IMPELLER	SPCC METAL
DIMENSION	92*92*38 mm
WEIGHT	0.43 KG.