

XHD4020B24H DC24V 帶線風扇

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Size : 40*40*20mm

Frame : Plastic PBT(UL:94V-0)

Impeller : Plastic PBT(UL:94V-0)

Safety : CE/FC/UL

Net weight : 31.6g

Dielectric strength : 5mA max at 500V AC 60Hz 1 minute

Life expectancy : Sleeve Bearing 20000(Hrs) at 25°

Ball Bearing 50000(Hrs) at 25°

Operating temperature : Ball bearing: -30 °C ~+80°C

Sleeve bearing: -10 °C ~+70°C

M-DC-4020 散热风扇

型号 Model	电压 Voltage	电流 Current	功率 Power	转速 Speed	风量 Air flow		风压 Pressure		噪音 Noise	重量 Weight
PART No	VDC	Amp	Watt	R.P.M	m3/min	CFM	mmH2O	INH2O	dB-a	G
XHD4020S05H	5	0.21	1.05	7000	0.233	8.21	5.74	0.226	33	31.6
XHD4020B12M	12	0.12	1.44	7500	0.286	8.46	6.76	0.227	27	
XHD4020B24H	24	0.08	1.92	8500	0.329	9.45	9.1	0.374	31	