

彩色風雨型紅外線攝影機

特色：

- 攝像元件：SONY 1/3" CCD
- 總圖素：537(H) x 505(V)
- 最低照度：0.01 Lux (IR-ON 0 Lux)
- 解析度：420 條以上
- 訊噪比：48dB 以上
- 42顆紅外線LED，投射距離可達40M以上
- 鋁合金外殼及陽極處理,易於散熱
- 圖示之腳架以現場環境之需為(選配)



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

規格：

型號	KMS-D42IR	KMS-D42IRHN
攝像元件	SONY 1/3" CCD	
總圖數	537(V) x 505(H)	711(V) x 492(H)
掃描系統	525 條掃描線，60 圖場/秒	
同步系統	內/外同步	
最低照度	0.01LUX/F2.0 IR ON:0LUX	
水平解析度	420 TV Line	480 TV Line
白平衡	自動	
雜訊比	48 dB 以上	50dB 以上
電子快門	1/60 ~ 1/110,000 sec	1/50 ~ 1/110,000 sec
紅外線 LED	42 顆/850 nm	
IR 投射距離	40M 以上	
防水等級	IP66 以上	
標準鏡頭	4mm, 6mm, 8mm	
訊號輸出	1.0 V p-p at 75 Ω	
灰階校正	0.45	
工作溫度	-10°C ~ 50°C	
電源供應	DC 12V	
尺寸	72(Φ)X166(L) mm	

★注意:以上規格如有變更,不另行通知!

1/3" Waterproof Color Day & Night Camera (850nm) 30M KMS-D42IR

Features:

- 1/3" High resolution DSP Color CCD sensor
- completely built in aluminium with positive finishing triple heater
- Min. Illumination 2~3 lux (IR activation)
- IR built-in auto sensitive to B/W at night, complete for long time and outdoor used
- Power source DC12V 500mA
- moisture condensation-free on the glass against any harsh weather condition



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specification:

Model No	KMS-D42IR
Image sensor	SHARP CCD SENSOR 1/3"INTERLINE
Effective Pixels	NTSC 510(H)X491(V) PAL 512(H)X581(V)
Scanning system	NTSC standard 525 lines,30 frames/sec PAL standard 625 lines,25 frames/sec
Sync. Mode	Internal
Resolution	More Than 400TV Lines
Video Output	1.0 Vp-p / 75 Ohm
Gamma correction	0.45
Shutter speed	(1/60~1/110,000 sec) NTSC , (1/50~1/100,000 sec) PAL
Min. illumination	0.2 Lux F1.2/0 Lux IR ON
S/N Ratio	48dB (AGC OFF)
White Balance	Auto white balance (2000° K-10000°K)
Operating Temperature	-10 °C ~50 °C , -4 °F ~122 °F
IP Rate	IP66
Power source	DC12V±1.2 500mA
Power current	DC12V IR "ON" TOTAL: 400mA CAMERA: DC12v 90mA
LED spectrum	850 nm × 42pcs / 30M UP
Lens Option	Fit in F4 .0 mm,6.0mm , 8.0mm , 16mm lens
Measurement	72(Φ)X117(L) mm
Weight	630g

Installation:

- Follow the instruction hookup DC 12V, BNC or F connector into camera.
- Camera stand is optional (part no KMS-9044) , it may install into ceiling or wall.

★Caution:

1. Do not open the housing, warranty is void. It may cause electric shock or damage it.
2. If there has any hardware problem please content service person.
3. Please make sure the installation on stable.
4. Do not use any corrosiveness to clean camera, please turn off power and clean by dry cloth and less wet cloth.

CE IP 66

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)