

6,6URGJ

快速熔断器 Fast Fuses

- Voltage Rating 660V
- Current Rating 16-710A
- Breaking Capacity AC660V-100KA AC, DC (L/R10ms)
- Maximum arc voltage 1400V
- 额定电压660V
- 额定电流16~710A
- 分断容量660V-100KA AC, DC (L/R 10ms)
- 最大灭弧电压1400V

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



规格 Specifications

FS designation	Reference	Rated Current (A)	Pre-arc I ² t (A ² S)	Total I ² t (A ² S) at AC660V-100KA	Watts Loss (W)
6,6 URGJ 17/16	W280067	16	19	220	2.0
6,6 URGJ 17/20	X280068	20	26	310	3.5
6,6 URGJ 17/25	Y280069	25	42	440	4.0
6,6 URGJ 17/32	Z280070	32	74	770	6.0
6,6 URGJ 17/40	A280071	40	100	1100	7.0
6,6 URGJ 17/50	B280072	50	167	1600	9.0
6,6 URGJ 17/63	C280073	63	300	2700	12.0
6,6 URGJ 17/80	D280074	80	400	3800	17.0
6,6 URGJ 17/100	E280075	100	670	7400	22.0
6,6 URGJ 23/125	F280076	125	1200	10600	25.0
6,6 URGJ 23/160	G280077	160	2100	18000	35.0
6,6 URGJ 23/200	H280078	200	3300	29000	40.0
6,6 URGJ 31/250	J280079	250	6000	49500	50.0
6,6 URGJ 31/315	K280080	315	7400	63000	80.0
6,6 URGJ 37/350	L280081	350	11000	92000	70.0
6,6 URGJ 37/400	M280082	400	14000	112000	85.0
6,6 URGJ 237/450	N280083	450	24000	210000	85.0
6,6 URGJ 237/500	P280084	500	29000	270000	95.0
6,6 URGJ 237/630	Q280085	630	42000	390000	105.0
6,6 URGJ 237/710	R280086	710	51000	460000	115.0

● **CCC质量认证** CCC recognized products
 6,6URGJ-16-315。取得CCC公开的产品质量认证
 额定电压 : AC660V DC450V
 额定熔断电流: AC50KA DC50KA (时间常数15ms)

CCC recognized products are available at
 6,6URGJ-16 to 6,6URGJ-315.
 Rated voltage: AC660V DC450V
 Rated interrupting current : AC50KA DC50KA
 (Time constant 15ms)

● **熔断器夹** FUSE HOLDER HT6017
 熔断器夹安装。
 · 横向和连装均可。DIN相对应
 · 绝缘板可取出
 适用熔断器 6,6URGJ-16~100

