

General Purpose Fuses



French Ferrule

gG, aM

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw



DOMESTIC AND INDUSTRIAL CYLINDRICAL FUSE-LINKS

Ferraz Shawmut gF, gI-gG and aM fuse-links cover a wide range of physical sizes and ampere ratings for 250, 380*, 400, 500, and 660* volts AC. gF fuse-links are for domestic use. gI-gG and aM fuse-links are for industrial applications. Most ratings are available with an optional indicator. All industrial fuse-links have the option of a built-in striker. All cylindrical fuse-links have ceramic bodies and silver-plated ferrules.

* Fuse-links marked 380V (gF) and 660V (gI-gG-aM) will be re-marked (and safely used at) 400V AC and 690V AC in compliance with changes in IEC Standard 269, but should not be used above 418V AC or 726V AC.

gF

FULL RANGE PROTECTION

- ✓ 7 physical sizes from 6.3 x 23mm to 10.3 x 38 mm
- ✓ 250 and 380 Volt ratings - 0.5A through 32A
- ✓ Most ratings available with indicator
- ✓ Meet IEC, NFC, UNE and British standards
- ✓ See residential fuse-links, Special Purpose section

gG

FULL RANGE PROTECTION

- ✓ 4 physical sizes from 8 x 31mm to 22 x 58 mm
- ✓ 400, 500 and 690 Volt ratings - 0.5A through 125A
- ✓ Most ratings available with indicator
- ✓ Meet IEC, NFC and UNE standards
- ✓ Approved by Lloyds Register of Shipping and Bureau Veritas

gG

FULL RANGE PROTECTION

- Fuse-links with striker**
- ✓ 2 sizes- 14 x 51mm and 22 x 58mm
 - ✓ 400, 500 and 690 Volt ratings - 4A through 125A
 - ✓ All ratings include striker
 - ✓ Meet IEC, NFC and UNE standards
 - ✓ Approved by Lloyds Register of Shipping and Bureau Veritas

aM

SHORT CIRCUIT PROTECTION

- ✓ 4 physical sizes from 8 x 31mm to 22 x 58mm
- ✓ 400, 500 and 690 Volt ratings - 0.16A through 125A
- ✓ Most ratings available with indicator
- ✓ Meet IEC, NFC and UNE standards
- ✓ Approved by Lloyds Register of Shipping and Bureau Veritas

aM

SHORT CIRCUIT PROTECTION

- Fuse-links with striker**
- ✓ 2 sizes - 14 x 51mm and 22 x 58mm
 - ✓ 400, 500 and 690 Volt ratings - 2A through 125A
 - ✓ All ratings include striker
 - ✓ Meet IEC, NFC and UNE standards
 - ✓ Approved by Lloyds Register of Shipping and Bureau Veritas

General Purpose Fuses



French Ferrule

gI, gG

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Ratings – gI-gG (Optional Blown-Fuse Indicator)

SIZE (mm x mm)	RATED In CURRENT (A)	RATED VOLTAGE	CATALOG NUMBER		REFERENCE NUMBER		INTERRUPTING RATING (A)	STANDARD PACK/CTN.		
			w/o Indicator	w/Indicator	w/o Indicator	w/Indicator				
8 x 31	0.5	400V	15009	-	P218191	-	20kA - 400V	10		
	1		15011	-	C218709	-				
	2		15013	15213	Q219227	B222204				
	4		15019	15219	W222958	X222959				
	6		15023	15223	A211025	V201291				
	8		15027	15227	B213096	B211026				
	10		15031	15231	A214613	A212060				
	12		15033	15233	R216146	C213097				
	16		15035	15235	P216650	Y214105				
	20		15037	15237	F217677	J215127				
	25		15039	15239	D218710	S216147				
10 X 38	0.5	500V	16009	-	C211027	-	120kA - 500V	10		
	1		16011	-	B212061	-				
	2		16013	16213	D213098	S216653				
	4		16019	16219	X213598	E217170				
	6		16023	16223	K215128	T218195				
	8		16027	16227	D217169	V219231				
	10		16031	16231	S218194	E222207				
	12		16033	16233	W219761	H200751				
	16		16035	16235	G200750	H201809				
	20		16037	16237	D211028	X211551				
	25		16039	16239	E213099	W212585				
	32		400V	16043	16243	A214107			Z213600	120kA - 400V
	14 X 51	1	690V	17011	-	K218716	-	80kA - 690V	10	
2		17013		17213	Y219234	C201298				
4		17019		17219	A219765	H211032				
6		17023		17223	H222210	G212066				
8		17027		17227	D222965	K213104				
10		17031		17231	L200754	H214620				
12		17033		17233	L201812	R215640				
16		17035		17235	A211554	X216657				
20		17037		17237	Z212588	N217684				
25		17039		17239	C213603	M218718				
32		500V		17043	17243	W216656	C219767			120kA - 500V
40		500V		17047	17247	X218198	F222967			120kA - 500V
50		400V	17051	17251	Z219235	D201299	120kA - 400V			
22 x 58	2	690V	18013	-	F219241	-	80kA - 690V	10		
	4		18019	18219	H219772	Q211039				
	6		18023	18223	P222216	P212073				
	8		18027	18227	L222972	R213110				
	10		18031	18231	T200761	N214119				
	12		18033	18233	J201304	Y215140				
	16		18035	18235	S201818	D216157				
	20		18037	18237	P211038	R217181				
	25		18039	18239	N212072	F218206				
	32		18043	18243	F212594	H219243				
	40		18047	18247	J213609	R222218				
	50		18051	18251	P214626	W200763				
	63		18055	18255	Y215646	V201820				
	80		18059	18259	Q217180	K211563				
	100		500V	18063	18263	E218205			H212596	120kA - 500V
	125	400V	18065	18265	J219773	L213611	120kA - 400V			



X211551



M218718



K211563


Blown-Fuse Indicator



BEFORE



AFTER



Dimensions

FUSE SIZE	A	B	C
8 x 31	8.5	31.5	6.3
10 x 38	10.3	38	10.5
14 x 51	14.3	51	13.8
22 x 58	22.2	58	16.2

General Purpose Fuses



French Ferrule

gG with striker

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Ratings – gI-gG with Striker

SIZE (mm x mm)	RATED CURRENT In (A)	RATED VOLTAGE	CATALOG NUMBER	REFERENCE NUMBER	INTERRUPTING RATING (A)	STANDARD PACK/CTN.
14 X 51	2	500V	17413	J211033	120kA - 500V	10
	4		17419	H212067		
	6		17423	G214113		
	8		17427	R215134		
	10		17431	Z216153		
	12		17433	L217176		
	16		17435	Z218200		
	20		17437	B219237		
	25		17439	L222213		
	32		17443	P200757		
	40		17447	P201815		
	50		17451	D211557		
22 X 58	4	690V	18419	R214628	80kA - 690V	10
	6		18423	A215648		
	8		18427	F216665		
	10		18431	W217691		
	12		18433	W218726		
	16		18435	L219775		
	20		18437	P222975		
	25		18439	M201307		
	32		18443	S211041		
	40		18447	R212075		
	50		18451	M213612		
	63		18455	S214629		
NEUTRAL	80	500V	18459	F216159	120kA - 500V	10
	100	400V	18463	T217183		
	125		18465	H218208		
	10 x 38	19100	R211569			
	10 x 38	1920J	M212600J			
	10 x 38	1930	R213616			




P201815



R212075

Dimensions

FUSE SIZE	A	B	C	D	E
14 x 51	14.3	51	13.8	7.5	3.8
22 x 58	22.2	58	16.2	7.5	3.8



Striker




BEFORE



AFTER

- 1 Ceramic body
- 2 Sand
- 3 Indicator contact
- 4 Lower contact
- 5 Contact ring
- 6 Melting element
- 7 Indicator



General Purpose Fuses




French Ferrule

gG


勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Characteristics t-I



Prospective current (r.m.s. A)

Cut-off characteristics



Prospective current (KA eff)

General Purpose Fuses



French Ferrule

gG

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Characteristics I²t






Table temperature increase (testing in superior contact)



General Purpose Fuses



French Ferrule

gG

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Power loss table

In	Size		
	10 x 38	14 x 51	22 x 58
0,5 A	2 W		
1 A	2,5 W	3,4 W	
2 A	0,70 W	1 W	1,20 W
4 A	0,80 W	1,10 W	1,30 W
6 A	0,90 W	1,20 W	1,40 W
8 A	1,10 W	1,50 W	1,65 W
10 A	1,35 W	1,80 W	2 W
12 A	1,55 W	2,10 W	2,40 W
16 A	1,90 W	2,55 W	3 W
20 A	2,30 W	3 W	3,40 W
25 A	2,80 W	3,50 W	3,80 W
32 A	3 W	3,80 W	4,30 W
40 A		4,40 W	5,10 W
50 A		4,7 W	5,50 W
63 A			6,70 W
80 A			8 W
100 A			9 W
125 A			12,5 W

IEC 269-2-1	10 x 38	14 x 51	22 x 58
NFC 63.213	25 A	40 A	100 A
UNE 21.103-2-1	3 W	5 W	9,5 W

Table of maximum longitudes of network in function of In and conductor section

gG CLASS FUSES

Copper conductor section (mm ²)	RATED CURRENT (In) OF gG FUSES (in A)									
	16	20	25	32	40	50	63	80	100	125
1,5	99/113	86/87	40/59	21/29	13/16	7/9				
2,5		134	110/122	67/84	41/51	25/33	13/20	8/11		
4			183	139	108/119	67/84	46/58	24/32	14/17	7,3/10
6				214	165	139	94/113	55/70	33/41	20/27
10					275	226	172	130	90/108	57/70
16							283	217	168	128
25								336	257	197
35									367	283
50										379

* 99/118:

- 99; Cond. PVC / 118; Cond. PRC