



80x80x25mm

- Airflow: 27.9~59.8 CFM
- Static Pressure: 1.3~5.4 mm-H₂O
- Blade / Housing:
Plastic Material UL 94V-0 P.B.T.
- Lead Wire: UL1007 #24 AWG
- Weight: 88 g

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)

Model No.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Max. Airflow	Max. Static Pressure	Current	Power Consumption	Life at 40°C L10	P-Q Curve	Noise Level
		VDC	VDC	RPM	CFM	mm-H ₂ O	mA	W	Hour		dB(A)
GD128025LS	S		7~13.2	1900	27.9	1.3	100	1.20	30000	5	22.5
GD128025MS	S		7~13.2	2400	35.4	2.1	160	1.92	30000	4	27.5
GD128025HS	S		7~13.2	2900	43.7	2.9	230	2.76	25000	3	33.5
GD128025ES	S		7~13.2	3200	47.4	3.6	260	3.12	20000	2	36.0
GD128025LB	2B		7~13.2	2000	30.0	1.5	100	1.20	80000	5	23.5
GD128025MB	2B	12	7~13.2	2500	37.0	2.1	160	1.92	80000	4	30.0
GD128025HB	2B		7~13.2	3000	45.2	3.1	230	2.76	75000	3	34.5
GD128025EB	2B		7~13.2	3300	48.5	3.8	260	3.12	65000	2	37.0
GD128025EB	2B		7~13.2	4000	59.8	5.4	510	6.12	65000	1	43.0
GD248025LB	2B		12~26.4	2000	30.0	1.5	60	1.44	80000	5	23.5
GD248025MB	2B	24	12~26.4	2500	37.0	2.2	80	1.92	80000	4	30.0
GD248025HB	2B		12~26.4	3000	45.2	3.1	130	3.12	75000	3	34.5
GD248025EB	2B		12~26.4	3300	48.5	3.8	150	3.60	65000	2	37.0
GD488025LB	2B		24~56.0	2000	30.0	1.5	40	1.44	80000	5	23.5
GD488025MB	2B	48	24~56.0	2500	37.0	2.2	50	2.40	80000	4	30.0
GD488025HB	2B		24~56.0	3000	45.2	3.1	90	4.32	75000	3	34.5

2B: 2-ball bearing BS: 1-ball 1-sleeve bearing L: sintetico bearing S: sleeve bearing

Voltage Available

Bearing System Available

Function Available

05 12 24 48

2B L S

N A I F R Q S T M V C P D W U

PERFORMANCE P-Q CURVE

OUTLINE DIMENSIONS

