

## KLKD 10x38 mm MIDGET FUSE



### Product Features

- UL Listed 600 Vdc maximum
- 50,000 Adc interrupting rating
- High performance in compact 10x38 mm midget size
- Touch-safe DIN-rail mount holder available
- PCB leaded version available in select amperages (Contact factory for availability)

### Description

The KLKD series is a fast acting, high interrupting capacity, current limiting type fuse. It is perfect for 600 Vdc applications such as photovoltaic systems.

### Specifications

- Voltage Rating:** 600 Vac/dc  
**Interrupting Rating:** AC: 100,000 A rms symmetrical;  
 DC: 50,000A  
**Dimensions:**  $1\frac{3}{32}$ " x  $1\frac{1}{2}$ " (10x38 mm)  
**Approvals:** Standard 248-14  
 UL Listed 3/10-30 A (File No: E10480)  
 CSA Certified 3/10-30 A (File No: LR29862)  
**Environmental:** RoHS Compliant  
 Lead (Pb) Free

### AMPERE RATING

$\frac{1}{10}$	1	5	15
$\frac{1}{8}$	1½	6	20
$\frac{3}{10}$	2	7	25
$\frac{1}{4}$	2½	8	30
$\frac{3}{10}$	3	9	
$\frac{1}{2}$	3½	10	
$\frac{3}{4}$	4	12	

### Ordering Example

CATALOG NUMBER	SYSTEM NUMBER	AMPERAGE
KLKD.300	KLKD.300T	3/10
KLKD002	KLKD002.T	2
KLKD030	KLKD030.T	30
KLKD030R	KLKD030.HXR	30 (with PCB tabs)


### Recommended Fuseholder

LPHV

### Web Resources

Downloadable CAD drawings and other technical information:  
[www.littelfuse.com/klkd](http://www.littelfuse.com/klkd)

### Dimensions in inches (mm)



### Dimensions in inches - PCB Version (mm)

