

直插自恢复保险丝

SR16 代表耐压 **16V** **SR30**=耐压 **30V** **SR60**=耐压 **60V** **SR250**=耐压 **220-250V**

(注:SR 代表品牌,品牌不同前面字符标识不同,规格一样是通用的.)

规格认识:**0.1A=100MA/毫安**,以此类推.

规格	参数 (P=脚距)	规格	参数 (P=脚距)
HR16-160	1.6A/16V P=5MM	SR30-020	0.2A/30V P=5MM
SR16-300	3A/16V P=5MM	SR30-090	0.9A/30V P=5MM
SR16-400	4A/16V P=5MM	SR30-110	1.1A/30V P=5MM
SR16-500	5A/16V P=5MM	SR30-135	1.35A/30V P=5MM
SR16-600	6A/16V P=5MM	SR30-160	1.6A/30V P=5MM
SR16-700	7A/16V P=5MM	SR30-185	1.85A/30V P=5MM
SR16-800	8A/16V P=5MM	SR30-250	2.5A/30V P=5MM
SR16-900	9A/16V P=5MM	SR30-300	3A/30V P=5MM
SR16-1000	10A/16V P=5MM	SR30-400	4A/30V P=5MM
SR16-1100	11A/16V P=5MM	SR30-500	5A/30V P=10MM
SR16-1200	12A/16V P=10MM	SR30-600	6A/30V P=10MM
SR16-1400	14A/16V P=10MM	SR30-700	7A/30V P=10MM
		SR30-800	8A/30V P=10MM
SR60-005	0.05A/60V P=5MM	SR30-900	9A/30V P=10MM
SR60-010	0.1A/60V P=5MM		
SR60-017	0.17A/60V P=5MM	SR250-050	0.05A/250V P=5MM
SR60-020	0.2A/60V P=5MM	SR250-060	0.06A/250V P=5MM
SR60-025	0.25A/60V P=5MM	SR250-080	0.08A/250V P=5MM
SR60-030	0.3A/60V P=5MM	SR250-100	0.1A/250V P=5MM
SR60-040	0.4A/60V P=5MM	SR250-110	0.11A/250V P=5MM
SR60-050	0.5A/60V P=5MM	SR250-120	0.12A/250V P=5MM
SR60-065	0.65A/60V P=5MM	SR250-145	0.145A/250V P=5MM
SR60-075	0.75A/60V P=5MM	SR250-180	0.18A/250V P=5MM
SR60-090	0.9A/60V P=5MM	SR250-200	0.2A/250V P=5MM
SR60-110	1.1A/60V P=5MM	SR250-400	0.4A/250V P=5MM
SR60-135	1.35A/60V P=5MM	SR250-600	0.6A/250V P=5MM
SR60-160	1.6A/60V P=5MM	SR250-800	0.8A/250V P=5MM
SR60-185	1.85A/60V P=5MM	SR250-1000	1A/250V P=5MM
SR60-250	2.5A/60V P=10MM		
SR60-300	3A/60V P=10MM		
SR60-375	3.75A/60V P=10MM		