

電磁接觸器/電磁開關機種容量一覽表

P11~P25型



勝特力材料 886-3-5753170
 胜特力电子(上海) 86-21-54151736
 胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

機種				P11	P12	勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw					P15	P16	P21	P21A	P25
型 名	電磁接觸器			非可逆	S-P11(S)	S-P12(S)		S-P15(S)	S-P16(S)	S-P21(S)	S-P21A(S)	S-P25(S)			
				可逆	S-2XP11(S)	S-2XP12(S)		S-2XP15(S)	S-2XP16(S)	S-2XP21(S)	—	S-2XP25(S)			
	電磁開關	開放型	非可逆	MSO-P11(S)	MSO-P12(S)		MSO-P15(S)	MSO-P16(S)	MSO-P21(S)	MSO-P21A(S)	MSO-P25(S)				
			可逆	MSO-2XP11(S)	MSO-2XP12(S)		MSO-2XP15(S)	MSO-2XP16(S)	MSO-2XP21(S)	—	MSO-2XP25(S)				
		箱型	非可逆	MS-P11(S)	MS-P12(S)		MS-P15(S)	MS-P16(S)	MS-P21(S)	MS-P21A(S)	MS-P25(S)				
			可逆	MS-2XP11(S)	MS-2XP12(S)		MS-2XP15(S)	MS-2XP16(S)	MS-2XP21(S)	—	MS-2XP25(S)				
		箱型附按鈕	非可逆	MS-P11PB(S)	MS-P12PB(S)		MS-P15PB(S)	MS-P16PB(S)	MS-P21PB(S)	MS-P21APB(S)	MS-P25PB(S)				
熱過載繼電器（二素子/三素子/欠相型）				TH-P12(S)	TH-P12(S)		TH-P12(S)	TH-P18(S)	TH-P18(S)	TH-P18(S)	TH-P18(S)	TH-P20(TA)(S)			
額 定 容 量	CNS C4084 JIS C8325 JEM 1038	AC3 級額 定容量 (kW/A)	單相	100~110V	0.55/12	0.55/12		0.75/16	0.75/16	1.1/24	1.1/24	1.3/26			
				200~220V	1.1/12	1.1/12		1.5/16	1.5/16	2.2/24	2.2/24	2.6/26			
			三相	200~220V	3/12	3/12		3.7/16	3.7/16	5.5/24	5.5/24	6.5/26			
				380~440V	4/9	4/9		5.5/12	5.5/12	11/21	11/21	12/23			
				500~550V	4/7	4/7		5.5/10	5.5/10	11/17	11/17	12/20			
		AC 1級電阻性負載額定容量(A)			20	20		30	30	40	40	40			
		連續通電電流(Ith) (A)			20	20		30	30	40	40	40			
	IEC 60947-4-1 EN 60947-4-1 DIN VDE 0660	AC3 級額 定容量 (kW/A)	三相	240V	3.5/13	3.5/13		4.5/18	4.5/18	5.5/24	5.5/24	6.5/26			
				440V	5.5/12	5.5/12		7.5/16	7.5/16	11/21	11/21	12/23			
				550V	5.5/9	5.5/9		7.5/13	7.5/13	11/17	11/17	12/20			
				660V	5.5/7	5.5/7		7.5/9	7.5/9	11/14	11/14	12/16			
		AC 1級電阻性負載額定容量(A)			20	20		30	30	32	32	32			
		連續通電電流(Ith) (A)			20	20		30	30	32	32	32			
		UL 508 CSA-C22.2	FLA 額定容量 (HP/A)	單相	110~120V	0.5/9.8	0.5/9.8		1/16	1/16	2/24	2/24	2/24		
	220~240V				2/12	2/12		3/17	3/17	3/17	3/17	3/17			
	三相			220~240V	3/9.6	3/9.6		5/15.2	5/15.2	7.5/22	7.5/22	10/28			
				440~480V	7.5/11	7.5/11		10/14	10/14	15/21	15/21	15/21			
				550~600V	10/11	10/11		10/11	10/11	15/17	15/17	15/17			
	AC 1級電阻性負載額定容量(A)			24	24		30	30	35	35	40				
	連續通電電流(Ith) (A)			24	24		30	30	35	35	40				
	NEMA 等級				00	00		0	0	1	1	1			
補 助 接 點	接點構成	標準	非可逆	1a	1a1b		1a	1a1b	1a1b	2a2b	1a1b				
			可逆	2x1b	2x1a1b		2x1b	2x1a1b	2x1a1b	2x2a2b	2x1a1b				
	IEC 60947-4-1 EN 60947-4-1 額定電流(A)	AC12級 交流抵抗負載	110V	6	6		6	6	6	6	6				
			220V	5	5		5	5	5	5	5				
			440V	3	3		3	3	3	3	3				
			550V	3	3		3	3	3	3	3				
			連續通電電流(Ith) (A)		16	16		16	16	16	16	16			
補助接點等級(UL)			A600	A600,P600		A600	A600,P600	A600,Q300	A600,Q300	A600,Q300					
性 能	機械壽命/電氣壽命(AC3級)			(萬次)	500/100	500/100		500/100	500/100	500/100	500/100	500/100			
	開閉頻度			(次/小時)	1200	1200		1200	1200	1200	1200	1200			
附 屬 裝 置	補助接點組	上裝式	2P	2a、1a1b、2b	○	○		○	○	○	○	○			
			4P	4a、3a1b、2a2b	○	○		○	○	○	○				
		側裝式		1a1b		○	○		○	○	○	○			
	線圈突波吸收器(外裝式AC240V以下適用)				○	○		○	○	○	○				
	機械連鎖組				MPU-11	MPU-21		MPU-11	MPU-21	MPU-21	MPU-21	MPU-21			

註：P11~P150型寬電壓專用50Hz規格可另訂貨生產

*註：S為附加保護蓋型