











Size 000 DIN - 690V gRB - URB

Protistor® DIN 80mm standard fuse sizes 000-00



Current (A)	Curves	Cat.Number for bracket-style with striker	Ref. number for bracket-style with striker	Pckg
16	gRB	DN000GB69V16L	X330277C 	3
20	gRB	DN000GB69V20L	J330173C 	3
25	gRB	DN000GB69V25L	K330174C 	3
32	gRB	DN000GB69V32L	L330175C 	3
40	gRB	DN000GB69V40L	M330176C 	3
50	gRB	DN000GB69V50L	N330177C 	3
63	gRB	DN000GB69V63L	P330178C 	3
80	gRB	DN000GB69V80L	Q330179C 	3
100	gRB	DN000GB69V100L	R330180C 	3
125	gRB	DN000GB69V125L	S330181C 	3
80	URB	DN000UB69V80L	T330182C	3
100	URB	DN000UB69V100L	V330183C	3
125	URB	DN000UB69V125L	W330184C	3
160	URB	DN000UB69V160L	X330185C	3
200	URB	DN000UB69V200L	Y330186C	3
250	URB	DN000UB69V250L	Z330187C	3
315	URB	DN000UB69V315L	A330188C	3
350	URB	DN000UB69V350L	B330189C	3
400	URB	DN000UB69V400L	F330193C	3
Micro (1)		MS4L2-5B6PRES	F210156C	3

For Blade style - see gS page 98

(1) : Microswitch automatically resattable, indicates fuse presence (PRES) and proper mounting. In case of improper mounting or fuse melting this is indicated (terminal 1-4 closed)
 Clips 6.3 mm