

產品型號: BS-2AG13-9SMT

型號: 適用於 AG13 電池

塑膠材質: PPA 料 (耐溫 240°~260°)

五金材質: 磷青銅

電鍍處理方式: Au1U"

裝箱規格: 10 只 x10 行=100 只每盤 (吸塑盤裝) 一
箱 100 只/盤 x8 盤 1 小盒, 4 小盒 x800 只=3200 只
外箱

毛重: 6.2KGS 淨重: 3.8KGS



裝箱尺寸:40x26x28.5CM

適用範圍: 醫療設備 數碼玩具 工控主機板 消防等








REV.	REV. NO.	REVISED	DATE



NOTE:
 1.MATERIAL:
 a.HOUSING:PPA
 b.CONTACT:PHOSPHOR BLACK
 (SURFACE PLATING:A*U*)
 SEE ORDERING INFORMATION
 2.ELECTRIC:
 a.CONTACT RESISTANCE: 30 MILLIOHMS MAX
 b.INSULATION RESISTANCE: 1000 MEGA OHMS MIN
 c.DIELECTNIC VOLTAGE: 500V AC ONE SEC LEVEL
 d.OPERATING TEMPERATURE: -25°C~ +85°C



PCB Layout Diagram
Top View

ORDERING INFORMATION

BS-09-B***001

电池座系列
BS-9系列
SMT 180° TYPE

PLATING:
A-Au1U*
J-NI100U**120U*
K-SN100U**120U*

MATERIAL:
1A-PBT BLACK
1B-PA66 BLACK
2A-PPA BROWN
2B-PPA BLACK
3A-PPS BROWN
3B-PPS BLACK
4A-LCP WHITE
4B-LCP BLACK



UNLESS OTHERWISE SPECIFIED TOLERANCES		MYOUNG 美阳 www.meiyangdz.com		SCALE: 1:1		SIZE: A4	VIEW:	PART NO:
FRONT VIEW	±0.30	ANGLE	±0.1°	UNIT: mm	REV: A/0	OBJECT: MY	DATE: 2014.10.19	BS-09-B2AA001
TOP VIEW	±0.25	CHORD	±0.5°	DATE: 2014.10.19	DATE: 2014.10.19	DATE: 2014.10.19	TITLE:	BS-2AG13-9SMT
RIGHT VIEW	±0.20	WEIGHT: 1.75 g	DATE: 2014.10.19	CHKD: ZhouKuiGai	DATE: 2014.10.19	DATE: 2014.10.19		
LEFT VIEW	±0.10	SHEET 1 OF 1	DATE: 2014.10.19	APVD: YueZhengy	DATE: 2014.10.19	DATE: 2014.10.19		

NO.	PART NAME	QTY	MATERIAL	PLATING & COLOR
3	TERMINAL (-)	1	PHOSPHOR BRONZE, 1*0.30MM	Gold Plating and Ni Under-Plating
2	TERMINAL (-)	1	PHOSPHOR BRONZE, 1*0.30MM	Gold Plating and Ni Under-Plating
1	HOUSING	1	PPA	BLACK