

F20T12/CW/ECO6PK

- Passes TCLP, which can lower disposal costs.

Bulb	T12
ANSI Code	2015-1
Base	Medium Bi-Pin (G13)
Wattage	20
Voltage	57
Initial Lumens	1200
Color Temperature	4100 K
Color Rendering Index (CRI)	60
Rated Life	9000 hrs
Product Code	80046
Description	F20T12/CW/ECO6PK
UPC	043168980517
Primary Application	Standard

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

F34CWRS/WM/ECO-S

GENERAL CHARACTERISTICS

Lamp type	Linear Fluorescent - Straight Linear
Bulb	T12
Base	Medium Bi-Pin (G13)
Wattage	34
Voltage	79
Rated Life	20000 hrs
Bulb Material	Soda lime
Starting Temperature (MIN)	16 °C (61 °F)
LEED-EB MR Credit	109 picograms Hg per mean lumen hour
Additional Info	TCLP compliant
Primary Application	Standard

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	2650
Mean Lumens	2280
Nominal Initial Lumens per Watt	77
Color Temperature	4100 K
Color Rendering Index (CRI)	60

ELECTRICAL CHARACTERISTICS

Open Circuit Voltage (rapid start) (MAX)	330 V
Open Circuit Voltage (rapid start) Min @ Temperature	256 V @ 10 °C
Cathode Resistance Ratio - Rh/Rc (MIN)	4.25
Cathode Resistance Ratio - Rh/Rc (MAX)	6.5
Current Crest Factor (MAX)	1.7

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)