

Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	Base Type	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila- ment Type	LCL (mm)	MOL (mm)	Burning Position	Bulb Finish	Fig. No.
Table 13: Halogen, Single-Ended, GY16 2-Pin Prefocus (16mm Apart)																		
2000	G-13	FTM	62	FTM	CP43	20309	12	GY16	230	3200	400	54000	C-13	70	145	BDTH		19
		FTL	62	FTL	CP43	20310	12	GY16	240	3200	400	54000	C-13	70	145	BDTH		19
		CP79	62		CP79	90360	12	GY16	120	3200	350	54000	C-13D	70	145	BDTH		19*
		CP79	62		CP79	30497	12	GY16	230	3200	350	54000	C-13D	70	145	BDTH		19
		CP79	62		CP79	30498	12	GY16	240	3200	350	54000	C-13D	70	145	BDTH		19

Table 14: Halogen, Single-Ended, G22 Medium Bi-post (22mm Apart)																		
500	T-8	EGN-Q500T8	62	EGN	—	30373	12	G22	120	3200	150	13000	C-13	64	140	BDTH		20
650	T-8	FKH	62	FKH	CP39	20320	12	G22	230	3200	100	16900	C-13	64	140	BDTH		20
		FKH	62	FKH	CP39	20321	12	G22	240	3200	100	16900	C-13	64	140	BDTH		20
750	T-7	EGR-Q750T7/4CL	1, 62	EGR	—	39190	12	G22	120	3200	200	21000	C-13D	64	127	BDTH		20

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Watts	Bulb OD	GE Description	Footnotes/ Safety Notices	ANSI Code	LIF Code	Product Order Code	Std. Pack Qty.	Base Type	Design Volts	Design Color Temp (K)	Rated Life (hrs)	Initial Design Lumens	Fila- ment Type	LCL (mm)	MOL (mm)	Burning Position	Bulb Finish	Fig. No.
Table 14: Halogen, Single-Ended, G22 Medium Bi-post (22mm Apart) (continued)																		
1000	T-7	EGT-Q1000T7/4CL	1, 62	EGT	—	39191	12	G22	120	3200	250	28500	C-13D	64	127	BDTH		20
	T-8	FKJ	62	FKJ	CP40	39655	12	G22	230	3200	200	26000	C-13	64	140	BDTH		20
		FKJ	62	FKJ	CP40	20286	12	G22	240	3200	200	26000	C-13	64	140	BDTH		20
1200	T-8	OC1200	62			91580	12	G22	80	3300	300	37500	C-13D	64	140	BDTH		20
	G-11	CP93	62		CP93	30384	12	G22	240	3200	200	33000	C-13D	64	140	BDTH		21
2000	G-13	CP92	62		CP92	30391	12	G22	120	3200	400	55000	C-13D	90	175	BDTH		22
		CP92	62		CP92	30394	12	G22	230	3200	400	52000	C-13D	90	175	BDTH		22
		CP92	62		CP92	30397	12	G22	240	3200	400	52000	C-13D	90	175	BDTH		22
2500	G-13	CP91	62		CP91	30415	12	G22	230	3200	400	67500	C-13D	90	175	BDTH		22
		CP91	62		CP91	30423	12	G22	240	3200	400	67500	C-13D	90	175	BDTH		22

Table 15: Halogen, Single-Ended, G38 Mogul Bi-post																		
1000	T-7	CYV-Q1000T7/4CL/BP	1, 62	CYV	—	42697	6	G38	120	3200	200	28500	C-13D	127	203	BDTH		23
1500	T-10	CXZ-Q1500T10/4CL	1, 62	CXZ	—	37564	6	G38	120	3200	400	44500	C-13	127	216	BDTH		23
2000	T-10	CYX-Q2000T10/4CL	1, 62	CYX	—	36636	6	G38	120	3200	350	59000	C-13	127	216	BDTH		23
	G-10	FKK	62	FKK	CP41	31844	12	G38	230	3200	400	54000	C-13	127	216	BDTH		23

Lamp stocking color code: EUROPE ONLY, EUROPE and NORTH AMERICA, NORTH AMERICA ONLY