

Technische Daten

Technical data

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)

Modell Model	Typ Type	Nennspannung Voltage (V)	Leistung Wattage (W)	Sockel Base	Lichtstrom Luminous flux (lm)	Lebensdauer Life (h)	LK Abmessungen LK dimensions * (mm)	Brennstellung Operating position	e - E-Maß Light center length (mm)	d - Durchmesser Bulb diameter (mm)	l - Länge Total length (mm)	Figur Figure
Halogenlampen mit Jostiersockel Halogen lamps with pin-focus base												
HLW5	HLW5	5	30	PY16-1,25	650	150	0,9 x 1,7	s90	1,25 nom.	9,0 max.	30,0 max.	1**
HLW5	HLW5	6	10	PY16-1,25	195	100	1,9 x 0,5	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5	6	10	PY16-1,25	150	100	1,2 x 1,1	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5	6	20	PY16-1,25	450	100	1,9 x 1,4	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5-A	6	25	PY16-1,25	510	100	1,7 x 1,7	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5	6	25	PY16-1,25	525	75	2,7 x 1,2	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5-A	6	30	PY16-1,25	660	100	1,7 x 1,7	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5-A	12	20	PY16-1,25	350	1000	1,9 x 1,9	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5	12	35	PY16-1,25	800	1000	3,2 x 1,6	s90	1,25 nom.	9,0 max.	30,0 max.	1
HLW5	HLW5	12	50	PY24-1,5	1400	50	3,3 x 1,9	s90	36,0 nom.	11,0 max.	53,0 max.	2
HLW5	HLW5-A	12	50	PY24-1,5	1400	50	2,2 x 2,4	s90	36,0 nom.	11,0 max.	53,0 max.	2
HLW5	HLW5	12	100	PY24-1,5	3000	50	4,2 x 2,3	s90	36,0 nom.	11,0 max.	53,0 max.	2
HLW5	HLW5-A	12	100	PY24-1,5	3000	50	3,1 x 3,1	s90	36,0 nom.	11,0 max.	53,0 max.	2
HLW5	HLW5	24	150	PY24-1,5	5000	50	5,8 x 3,1	s90	36,0 nom.	12,5 max.	59,0 max.	2
HLW5	HLW5-P	24	200	PY24-1,5	5500	300	4,5 x 6,4	s90	40,0 nom.	13,5 max.	55,0 max.	3
Halogenlampen mit hochwärmefesten Stiften (platinisiert) Halogen lamps with high temperature-resistant pins (platinized)												
HLW5	HLW5	6	10	G4	195	100	1,9 x 0,5	s90	19,5 nom.	9,0 max.	30,0 max.	4
HLW5	HL	6	20	G4	300	1000	2,0 x 2,0	b	19,5 nom.	9,0 max.	30,0 max.	4
HLW5	HLW5	6	20	G4	450	100	1,9 x 1,4	b	19,5 nom.	9,0 max.	30,0 max.	4
HLW5	HL	12	23	G4	500	100	3,1 x 0,8	s90	19,5 nom.	9,0 max.	30,0 max.	4
HLW5	HL	12	20	G4	300	2000	3,5 x 0,85	b	19,5 nom.	9,0 max.	30,0 max.	4
HLW5	HL	12	20	G4	350	1000	1,9 x 1,9	b	19,5 nom.	9,0 max.	30,0 max.	4
HLW5	HLW5	12	50	G6,35-15	1400	50	3,3 x 1,6	s90	30,0 nom.	11,0 max.	44,0 max.	5
HLW5	HL3	12	50	G6,35-15	900	2000	4,9 x 1,7	b	30,0 nom.	11,0 max.	44,0 max.	5
HLW5	HL	12	50	G6,35-15	1000	2000	3,5 x 2,4	b	30,0 nom.	11,0 max.	44,0 max.	5
HLW5	HLW5	12	100	G6,35-15	3000	50	4,2 x 2,3	s90	30,0 nom.	11,0 max.	44,0 max.	5
HLW5	HLW5	12	100	G6,35-15	2550	2000	4,9 x 3,1	s90	30,0 nom.	11,0 max.	44,0 max.	5
HLW5	HLW5-I	12	100	G6,35-15	3000	50	3,1 x 3,1	s90	33,0 nom.	11,0 max.	47,0 max.	5
HLW5	HLW5-I	12	50	G6,35-15	1400	50	2,2 x 2,4	s90	30,0 nom.	11,0 max.	44,0 max.	5
HLW5	HLW5	24	150	G6,35-15	5000	50	5,8 x 3,1	s90	32,0 nom.	12,5 max.	50,0 max.	5
HLW5	HLW5	24	150	G6,35-15	5000	300	6,2 x 3,2	s90	32,0 nom.	12,5 max.	50,0 max.	5
HLW5	HLPA	24	250	G6,35-20	8400	300	7,8 x 3,8	s90	33,0 nom.	13,5 max.	55,0 max.	5