



product details

41860 WFL 20W 12V GU5,3 FS1



Product description: 41860 WFL 20W 12V GU5,3 FS1
 Product code: 4050300012629
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Applications	
Dimmable	Yes
Burning position	any

Categorizations	
Sstl-Number	4739508
ILCOS	HRGS//UB-20-12-GU5,3-51/36

General Description	
Base (standard designation)	GU5.3
Mercury-free	Yes

Technical - Electrical Data	
Nominal wattage	20 W
Rated wattage	20 W
Nominal voltage (product)	12 V

Technical - Geometries	
Overall length	46.00 mm
Contact spacing	5.3 mm
Diameter	51.0 mm
Length	46 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Luminous intensity	510 cd
Beam angle	36 °
Color temperature	3000 K
Color rendering index Ra	100
Rated starting time	0 s

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300012629	Folding carton box contains 1 Piece	46,000 mm x 46,000 mm x 58,000 mm	30,000 g (0,000 g)	0,123 Cubic dec.
4050300499536	Shipping carton box contains 20 Piece	198,000 mm x 122,000 mm x 149,000 mm	676,000 g (0,000 g)	3,191 Cubic dec.





product details

41860 WFL 20W 12V GU5,3 FS1

Every professional knows that light is not always the same when it comes to illuminating heat-sensitive objects. In this case the DECOSTAR 51 dichroic reflector lamp is the right choice because most of the heat produced by the lamp is emitted through the rear of the reflector. This reduces the heat in the light beam by up to 66 %. It is therefore easier to present heat-sensitive objects in the right light.

- Brilliant accent light
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Low-pressure discharge vessel for use in open luminaires to IEC 60432-3
- Average life: 2,000 h
- Dimmable
- $R_a=100$
- Color temperature: 20 W - 2,800 K; 35 W - 2,900 K; 50 W - 2,950 K
- Base: GU5,3
- UV filter

For light distribution curves go to www.osram.com

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)