

Projection Lamps

ANSI Code	KONDO Type	Rated		Dimensions			Filament Type	Base	Approx. Lumens lm	Approx. Color Temp. K	Average Life h	S.P.	Fig. No.
		Volts	Watts	A mm	B Max. mm	C mm							
	KP-10	220, 230, 240, 250	100	32	135	55.5	CC-13	P28s	1500	2870	50	BD	1
	KP-10	220, 230, 240, 250	150	32	135	55.5	CC-13	P28s	2700	2920	50	BD	1
CVX/CVS	KP-10	100, 120	200	32	135	55.5	CC-13	P28s	4400	3100	25	BD	1
	KP-10	220, 230, 240, 250	250	32	135	55.5	CC-13	P28s	5100	3000	25	BD	1
CXY	KP-10	100, 120	300	32	135	55.5	C-13D	P28s	7300	3100	25	BD	1
CXK	KP-10 C-13	120	300	32	135	55.5	C-13	P28s	7400	3150	25	BD	1
DBF	KP-10	220, 230, 240, 250	300	32	135	55.5	CC-13	P28s	6600	3050	25	BD	1
CZX/DAB	KP-10	100, 120	500	32	135	55.5	C-13D	P28s	12500	3200	25	BD	1
DBT	KP-10	220, 230, 240, 250	500	32	135	55.5	C-13D	P28s	11400	3100	25	BD	1
DDB	KP-12	100, 120	750	38	144	55.5	C-13D	P28s	19500	3200	25	BD	1
DDY	KP-12 H2	120	750	38	144	55.5	C-13D	P28s	17000	2950	200	BD	1
DGH	KP-12 H5	120	750	38	144	55.5	C-13D	P28s	15000	3050	500	BD	1
DKK	KP-12	220, 230, 240, 250	750	38	144	55.5	C-13D	P28s	18000	3100	25	BD	1
DFT	KP-12	100, 120	1000	38	144	55.5	C-13D	P28s	27400	3250	25	BD	1
DFD	KP-12 NET	100, 120	1000	38	144	55.5	C-13D	P28s	31000	3350	10	BD	1
	KP-12	220, 230, 240, 250	1000	38	144	55.5	C-13D	P28s	25500	3150	25	BD	1
DKT	KP-12 10L	220, 230, 240, 250	1000	38	144	55.5	C-13D	P28s	29000	3250	10	BD	1
	KP-20	100, 120	500	64	144	55.5	C-13D	P28s	12500	3200	25	BD	2
DMX	KP-20 50HL	120	500	64	144	55.5	C-13	P28s	13200	3200	50	BD	2
	KP-20	220, 230, 240, 250	500	64	144	55.5	C-13D	P28s	11400	3100	25	BD	2
DPJ	KP-20	120	750	64	144	55.5	C-13D	P28s	19500	3200	25	BD	2
BFE	KP-20 H2	120	750	64	144	55.5	C-13D	P28s	17000	3000	200	BD	2
DRS	KP-20	100, 120	1000	64	144	55.5	C-13D	P28s	27400	3250	25	BD	2
DRC/DRB	KP-20 C-13	120	1000	64	144	55.5	C-13	P28s	28000	3250	50	BD	2
DWK	KP-20	220, 230, 240, 250	1000	64	144	55.5	C-13D	P28s	25500	3150	25	BD	2
CZS	KP-10 E	120	500	32	135	76	C-13D	E26	12500	3200	25	BD	3
DCX	KP-12 E	120	750	38	144	76	C-13D	E26	19500	3200	25	BD	3
EBP	KP-12 E	120	1000	38	144	76	C-13D	E26	27400	3250	25	BD	3
DLT	KP-20 E	30	500	64	144	76	C-13	E26	12500	3200	50	BD	4
DMS	KP-20 E/DMS	120	500	64	144	76	C-13	E26	13200	3200	50	BD	4
	KP-20 E	220, 230, 240, 250	500	64	144	76	C-13D	E26	11400	3100	25	BD	4
DPB	KP-20 E	120	750	64	144	76	C-13D	E26	19500	3200	25	BD	4
	KP-20 E	220, 230, 240, 250	1000	64	144	76	C-13D	E26	25500	3150	25	BD	4
DNS	KP-12	120	500	38	144	88.9	C-13D	P28s	11000	3200	200	BU	5
DEB	KP-12 H8	120	500	38	144	88.9	C-13D	P28s	9000	2850	800	BU	5




Fig.1




Fig.2




Fig.3




Fig.4



Fig.5

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)