

Specs. Lamp type	Voltage V	Wattage W	Luminous flux Lm	Average life hrs.	Color temp. °K	Max. overall length mm L ₁	Light length mm L ₂	Max. bulb dia. mm D	Base	ANSI code
JP230V800WCF ₁	230	800	20,000	150	3,200	120	70	φ11	RSC	EMF
JP240V800WC	240	800	20,000	250	3,200	120	70	φ11	RSC	—
JP240V800WCF	240	800	20,000	250	3,200	120	70	φ11	RSC	—
JP120V1000WC	120	1,000	25,000	150	3,200	127	80	φ11	RSC	—
JP120V1000WC ₁	120	1,000	25,000	200	3,200	120	68	φ11	RSC	FCM
JP120V1000WCF ₁ *	120	1,000	25,000	200	3,200	120	68	φ11	RSC	FHM
JP120V1000WC ₂	120	1,000	27,500	200	3,300	166	63	φ11	RSC	FFT
JP120V1000WC ₃	120	1,000	25,000	150	3,200	190	135	φ11	RSC	—
JP120V1000WS	120	1,000	30,000	30	3,400	127	55	φ11	RSC	—
JP220V1000WS	220	1,000	31,000	15	3,400	127	79	φ11	RSC	—
JP240V1000WS	240	1,000	30,000	20	3,400	127	70	φ11	RSC	DYC
JP220V1000WC	220	1,000	25,000	100	3,200	127	79	φ11	RSC	—
JP240V1000WC	240	1,000	25,000	150	3,200	127	75	φ11	RSC	—
JP120V1250WC	120	1,250	30,000	200	3,200	190	124	φ11	RSC	—
JP225V1250WC ₁	225	1,250	31,200	200	3,200	190	135	φ11	RSC	—
JP240V1250WC	240	1,250	30,000	200	3,200	190	125	φ11	RSC	—

* F Type: Frosted Finish

Note: RSC(R7S) is Recessed Single Contact

JPD20V170WC	20	170	4,250	100	3,200	58	10	φ9	RSC	FCK
JPD30V375W	30	375	6,750	1,000	2,900	78	12	φ14	RSC	DWZ
JPD120V420WC	120	420	10,500	75	3,200	65	13	φ15	RSC	FAL
JPD120V600WCG	120	600	17,000	75	3,250	68	15	φ15	RSC	FFJ
JPD120V600WD	120	600	15,600	100	3,200	93	15	φ15	RSC	FCB
JPD120V650WC	120	650	16,200	100	3,200	80	17	φ15	RSC	FAD
JPD120V650WCF *	120	650	16,200	100	3,200	80	17	φ15	RSC	FBX
JPD220V650WC	220	650	16,300	75	3,200	80	20	φ15	RSC	—
JPD230V650WC	230	650	16,300	75	3,200	80	20	φ14	RSC	—
JPD240V650WC	240	650	16,300	75	3,200	80	22	φ14	RSC	—
JPD120V650WS	120	650	20,000	20	3,400	80	15	φ15	RSC	DWY
JPD220V650WS	220	650	20,000	20	3,400	80	24	φ15	RSC	—
JPD240V650WS	240	650	19,500	20	3,400	80	23	φ14	RSC	—
JPD220V800WC ₁	220	800	20,000	75	3,200	80	25	φ15	RSC	DXX
JPD230V800WC	230	800	20,000	75	3,200	80	22	φ17	RSC	DXX
JPD240V800WC	240	800	20,000	75	3,200	80	30	φ14	RSC	DXX
JPD230V800WS	230	800	24,000	20	3,400	80	22	φ17	RSC	DXV
JPD240V800WS	240	800	22,000	20	3,400	80	30	φ15	RSC	DXV
JPD120V1000WC	120	1,000	25,000	150	3,200	94	23	φ17	RSC	—
JPD220V1000WC	220	1,000	25,000	120	3,200	94	26	φ17	RSC	—
JPD120V1000WC ₂	120	1,000	26,000	150	3,200	113	23	φ17	RSC	DYA
JPD120V1000WC ₄	120	1,000	26,000	150	3,200	145	21	φ17	RSC	—
JPD120V1000WC ₅	120	1,000	25,000	200	3,200	94	23	φ17	RSC	DXW
JPD120V1000WS ₁	120	1,000	31,000	30	3,400	94	22	φ17	RSC	DXN
JPD120V1050WS	120	1,050	28,000	75	3,200	118	22	φ17	RSC	ELJ
JPD120V2000WC	120	2,000	51,000	300	3,200	145	35	φ29	RSC	FEY
JPD225V2000WC ₁	225	2,000	50,000	300	3,200	145	37	φ29	RSC	FEX
JPD240V2000WC ₁	240	2,000	50,000	300	3,200	145	37	φ28	RSC	FEX
JPD120V2000WS	120	2,000	59,000	50	3,400	145	29	φ29	RSC	—

* F Type: Frosted Finish

Note: RSC(R7S) is Recessed Single Contact

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)