

## Item Information

### UL 1212, 1213; CSA 150V Wire- Extruded PTFE Insulation (Low voltage)

#### Item Number : 22-TE-1934-UL/CSA

Thin-wall extruded PTFE (Polytetrafluoroethylene) insulation for weight and space savings. The very thin wall insulation of these wires restricts their usage to low-voltage applications.

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Specifications

AWG Size	22
Conductor	Silver-Plated Copper
Stranding	19/34
Voltage rating - Volts	Not specified by UL; 150 for CSA.
Temperature rating - ° C	UL 1212: 80 UL 1213: 150 CSA: 200
Conductor Diameter - inches (mm)	.030 (.762)
Weight - pounds/1000 feet (Kg/1000 M)	3.51 (5.22)
Maximum Resistance - Ω/1000 feet (Ω/KM), @20 ° C	14.8 (48.5)
Insulation	Extruded PTFE, .008" (.20mm) wall thickness
Insulation Diameter - inches (mm)	.050 (1.27)
Ordering Information	Specify Thermax part number, UL or CSA style, and color.