

太陽電池規格一覽表 (室外)

型號 Type Model	尺寸, 毫米			電性		環境條件	備註
	寬	長	厚度	Vop, V	Iop, mA		
SC 5030	50.00	29.00	2.00	1.8	26.0	AM1 (100 mW/cm ²), 25°C	
SC 5848	57.80	48.20	2.00	8.0	8.0	AM1 (100 mW/cm ²), 25°C	
SC 7035	70.20	35.00	2.00	4.0	18.0	AM1 (100 mW/cm ²), 25°C	
SC 9728	96.80	28.00	2.00	6.0	15.0	AM1 (100 mW/cm ²), 25°C	
SC 12439	124.50	39.30	2.00	15.0	12.0	AM1 (100 mW/cm ²), 25°C	
SC 14633	145.70	32.50	2.00	9.6	13.0	AM1 (100 mW/cm ²), 25°C	
SP 0611 SC 60110Z	110.00	60.00	2.35	2.5	108.0	AM1 (100 mW/cm ²), 25°C	
SP 0907 SC 9070Z	89.70	69.70	2.35	4.0	50.0	AM1 (100 mW/cm ²), 25°C	
SP 1510 SC 14595Z	145.00	95.00	2.00	7.5	60.0	AM1 (100 mW/cm ²), 25°C	
SP 1515 SC 152152	152.40	152.4.00	2.35	7.5	120.0	AM1 (100 mW/cm ²), 25°C	
SP 3007 SC 29574Z	295.00	74.00	2.35	14.5	55.0	AM1 (100 mW/cm ²), 25°C	
SP 3030 SC 305305Z	304.80	304.80	2.35	17.0	177.0	AM1 (100 mW/cm ²), 25°C	
SM 8656	56.00	86.00	5.20	3.0	120.0	AM1 (100 mW/cm ²), 25°C	
SM 1143	108.00	43.00	3.00	9.0	30.0	AM1 (100 mW/cm ²), 25°C	
SM 9063	92.00	63.00	3.00	9.0	50.0	AM1 (100 mW/cm ²), 25°C	
SM 5055	60.00	65.00	5.20	2.5	150.0	AM1 (100 mW/cm ²), 25°C	
SM 5626	30.00	57.00	5.20	3.0	60.0	AM1 (100 mW/cm ²), 25°C	
SM 3015	118.00	176.00	8.00	14.5	120.0	AM1 (100 Mw/cm ²), 25°C	Power Module
SM 1530	118.00	176.00	8.00	7.5	200.0	AM1 (100 mW/cm ²), 25°C	Power Module
SM 1611	118.00	176.00	8.00	3.0	800.0	AM1 (100 mW/cm ²), 25°C	Power Module
SM 1212	110.00	115.00	3.60	0.5	3200	AM1 (100 mW/cm ²), 25°C	Power Module
SM 3412	121.00	346.00	16.00	6.0	800.0	AM1 (100 mW/cm ²), 25°C	Power Module
SM 3544	365.00	450.00	35.00	14.5	1000	AM1 (100 mW/cm ²), 25°C	Power Module

備註:

1. a:FI 200 Luxs, 25°C b:FL 300 Luxs, 25°C c:AMI(100Mw/cm), 25°C

2. 其他尺寸可依客戶需求做特殊設計

3. SC、SP 係非晶系列, SM 係單晶系列

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)