

(5W UL)Model No:GFP051U-Y SWITCHING POWER SUPPLY SPEC:



Model No:GFP051U-Y (U=UL/CUL, Y=0315, A315, 4207, 4212, 4505, 4510, 0505, 0510, 0610, 7508, 0965, 1205, 1504, 2425)

Above models were UL、CUL、PSE、BSMI approved,

Market:Japan, USA, Canada, Twain, Mexica

Dimension:46*33.2*23.4mm.

3V	3.3V	3.6V	4.2V	4.5V	5V	6V	7.5V	9V	12V	15V	24V
1.5A	1.5A	1.5A	0.7A	0.5A	0.5A	*	0.8A	0.65A	0.5A	0.4A	0.25A
2A	2A	*	1.2A	1A	1A	1A	*	*	*	*	*

Application

Lithium Ion Battery Charger

Digital Camera

CD-ROM HUB ADSL AP

Communication Terminals

Any Protable Device or Machine

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Input/Output Specifications

Input Voltage: AC 100-240V, 50/60Hz 0.2A

Range Voltage: AC 90--264V, 47/63Hz

Output Power : 5W

Output Voltage: 3V-24V

Over Voltage Protection: 120%min

Over Current Protection: 120%min

Short Protection: Auto Recovery

Load Regulation : $\pm 5\%$

General Specifications

Operating Temperature: 0~40 °C

Storage Temperature: -20~85 °C

Operating Relative Humidity: 5~95%RH

Withstanding Voltage: AC 2000V (Min), 5mA (Max)

Insulation Resistance: DC 500V 100M Ω (Min)