

DP-6016S 交換式直流電源供應器



功能特點：

- 大型背光液晶面版顯示
- 電壓/電流同時顯示
- 定電壓、定電流工作模式
- 高效率、重量輕、體積小
- 輸出 ON/OFF 開關控制
- ALM過溫保護功能

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

MODEL	DP-6016S
Input Voltage (Jumper Selection)	90~130 / 180~240VAC , 50Hz / 60Hz
Full Load Input Current at 230VAC	0.83A
Output Voltage Adjustable Range	1.0~60VC
Output Current Adjustable Range	0~1.6A
Voltage Regulation Load from 10% to 100% Variation Line from 180 to 264VAC Variation Ripple & Noise in r.m.s. Ripple & Noise (peak to peak)	50mV 30mV
Current Regulation Load from 10% to 100% Variation Line from 180 to 264VAC Variation Ripple & Noise (peak to peak)	20mA 20mA 20mA
Switching Operation Frequency	80KHz to 120KHz
Power Factor	0.68
Efficiency at Maximum Power	85%

Volt and Amp Potentiometer Type	Wire Wound 4 Digit
Voltmeter and Ammeter Display	
Voltmeter Accuracy	$\pm 1\%$ +5dgts for range $V \leq 5V$ $\pm 1\%$ +5dgts for range $V \leq 10V$ $\pm 1\%$ +5dgts for range $V \leq 20V$ $\pm 1\%$ +3dgts for range $V > 5V$ $\pm 1\%$ +3dgts for range $V > 10V$ $\pm 1\%$ +3counts for range $V > 20V$
Ammeter Accuracy	$\pm 1\%$ +5dgts for range $I \leq 2A$ $\pm 1\%$ +5dgts for range $I \leq 1A$ $\pm 1\%$ +5dgts for range $I \leq 0.5A$ $\pm 1\%$ +3dgts for range $I > 2A$ $\pm 1\%$ +3dgts for range $I > 1A$ $\pm 1\%$ +3dgts for range $I > 0.5A$
LCD Indication	CC, CV, Amp, Volt, Output ON-OFF
Protection	Short Circuit, Overload, Over Temperature, Tracking OVP
CE Approvals	LVD : EN 61010 , EMC : EN 55011
Cooling System	Natural Convection
Dimensions in mm (WxHxD)	70 x 150 x 250mm / 2.8 x 6.0 x 9.8in.
Weight in Kg	2Kgs / 4.4Lbs
Remarks	All the data are based on 230V 50Hz~60Hz

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)