

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>



Sparkle Power Inc.
A Leading Power Supply Manufacturer
Web site: www.sparklepower.com

SPI-300G (RoHS Compliant)
300 Watts AT/PS2 Switching Power Supply

Features

- Complied with AT standard
- High efficiency and reliability
- Internal 12V DC fan included
- Low noise and ripple
- Complies with FCC part 15 subpart J class B and CISPR 22 class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL60950-1, CSA C22.2 NO. 60950-1

Input Characteristics

Input Range: 90 ~ 132/180~264Vac (RMS), Manual Select

Frequency: 47 ~ 63Hz

Input Current: 6A (RMS) @115Vac, 3A (RMS) @230Vac

Inrush Current: 55A Max @132Vac cold start



Specification


- **Temperature Range:** Operating: 0°C ~ +40°C on full load; storage & shipping: -20°C ~ +65°C
- **Humidity:** 90% on operating and 95% storage
- **Dielectric Withstand:** Input to frame ground 1800 VAC for 1 second
- **Efficiency:** 65% at minimum measured at nominal AC main voltage and frequency with maximum load on all outputs
- **Rise time:** Less than 100mS on all Outputs
- **Hold-up Time:** 16.6ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **MTBF:** 50,000 hours on maximum load at +40°C
- **Dimensions (LxWxH):** 140x150x86mm/5.5x5.9x3.4in

Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+5V	3A	30A	± 5%	± 1%	50mV P-P
+12V	1A	12A	± 5%	± 1%	120mV P-P
-5V	0A	0.5A	± 10%	± 2%	150mV P-P
-12V	0A	0.5A	± 10%	± 2%	150mV P-P

* This subject power supply is 300W

REF. ID.	FIN NO.	SIGNAL	WIR. CODE	GAUGE	CONNECTOR TYPE	CABLE LENGTH
P8	1	COM	BLACK	18	MOLEX 90331 or EQV.	460±15mm
	2	COM	BLACK	18		
	3	-12VDC	BROWN	18		
	4	+12VDC	YELLOW	18		
	5	+5VDC	RED	18		
	6	P.G.	WHITE	18		
P9	1	+5VDC	RED	18	MOLEX 90331 or EQV.	460±15mm
	2	+5VDC	RED	18		
	3	+5VDC	RED	18		
	4	-5VDC	BLUE	18		
	5	COM	BLACK	18		
	6	COM	BLACK	18		
PA	1	+12V	YELLOW	18	AMP 1-480434-0430±15mm or EQV.	
	2	COM	BLACK	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
PB	1	+12V	YELLOW	22	AMP 171822-4 or EQV.	150±10mm
	2	COM	BLACK	22		
	3	COM	BLACK	22		
	4	+5V	RED	22		
PC	1	+12V	YELLOW	18	AMP 1-480434-0430±15mm or EQV.	
	2	COM	BLACK	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
PD	1	+12V	YELLOW	22	AMP 171822-4 or EQV.	150±10mm
	2	COM	BLACK	22		
	3	COM	BLACK	22		
	4	+5V	RED	22		
PE	1	+12V	YELLOW	18	AMP 1-480434-0430±15mm or EQV.	
	2	COM	BLACK	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		
PF	1	+12V	YELLOW	18	AMP 1-480434-0430±15mm or EQV.	
	2	COM	BLACK	18		
	3	COM	BLACK	18		
	4	+5V	RED	18		



NOTE:

1. ALL THE LENGTH OF
OUTPUT WIRES EXCLUDE HOUSING.

2 增加S/N, BAR CODE及删除S/N.&DATE CODE LABEL

UNIT:mm

MODEL NO. : SPI-300G(S032)	TITLE: ASSY	SHEET: 1 OF 1	REV: 02
R&D	PE	DRAWN	DATE
陳炳地	黃家駒	陳建基	MAY.23.2002
INTERIOR COUNTERSIGN:	陳建基		陳建基

Mechanical Drawing(外觀/機構圖) 表單編號7000P-0111