



Features

- DC to 2.2 GHz
- Flanged model
- Low VSWR
- Aluminum Nitride Ceramic

Applications

- High power RF transmission

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

CHF9838CNF Series 250 W Power RF Flanged Chip Termination


General Specifications

Substrate.....ALN
 Resistive Film.....Thick Film
 TabAg
 Tab AttachmentBraze with epoxy encapsulation
 Mounting FlangeCu plated with Ni
 Resistance.....50 Ω
 Tolerance $\pm 5\%$
 Packaging50 pcs./tray


Absolute Ratings

Power250 W
 Frequency2.2 GHz
 VSWR1.10 Maximum

Characteristic Curve



Product Dimensions



Asia-Pacific:

Tel: +886-2 2562-4117
 Fax: +886-2 2562-4116

Europe:

Tel: +41-41 768 5555
 Fax: +41-41 768 5510

The Americas:

Tel: +1-951 781-5500
 Fax: +1-951 781-5700

www.bourns.com

How To Order

CHF 9838 C N F 500 L

Model _____
 Size _____
 Version _____
 Substrate _____
 Mount _____
 F = Flange
 Value _____
 500 = 50 Ohm
 Function _____
 L = Termination