

Mounting brackets not included with resistors.

FEATURES

- Rugged lead free vitreous enamel coating
- All-welded construction.
- Self supporting terminal mounting option.
- Higher power ratings.
- Flame-resistant lead free vitreous enamel coating.
- RoHS compliant product available. Add “E” suffix to part number to specify.

**See page 36
for mounting hardware**

SPECIFICATIONS

Material

Coating: lead free vitreous enamel.

Core: Ceramic

Terminals: Tinned axial; RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

Derating: Linearly from 100% @ +25°C to 0% @ +350°C.

Electrical

Tolerance: 1Ω +: $\pm 5\%$
under 1Ω : $\pm 10\%$

Power rating: Based on 25°C free air rating.

Overload: 10 times rated wattage for 5 seconds.

Temperature coefficient:
5Ω and under: ±400 ppm/°C
Above 5Ω: ±260 ppm/°C


To calculate max. amps: use the formula $\sqrt{P/R}$.



勝特力材料 886-3-5753170
勝特力電子(上海) 86-21-34970699
勝特力電子(深圳) 86-755-83298787
[Http://www.100v.com.tw](http://www.100v.com.tw)

200 Series

Brown Devil® Vitreous Enamel Power



Series	Wattage	Ohms	Dimensions (in. / mm)			Lead Gauge	Max. Volt.*
			L	D	C		
B5	5.25	0.1-20K	0.625 / 15.88	0.250 / 6.35	0.135 / 3.43	20	187
B8	8.0	0.03-25K	1.000 / 25.40	0.313 / 7.94	0.188 / 4.76	18	250
B12	12.0	0.08-51K	1.750 / 44.45	0.313 / 7.94	0.188 / 4.76	18	625
B20	20.0	0.1-100K	2.000 / 50.80	0.438 / 11.11	0.250 / 6.35	18	750

Non-Inductive versions available. Insert "N" before tolerance code. **Example** - B5NJ10RE
Also available in low cost Centohm or Silicone coating. Consult Ohmite.
* Maximum Voltage is based on Ohm's Law [$V=\sqrt{P \times R}$] as limited by the resistance value of specified product

ORDERING INFO

Coating = Vitreous
Blank = Centohm
C = Centohm
S = Silicone

Wattage

Non-Inductive Winding
Optional (blank = std. winding)

RoHS Compliant

B 8 J 5 R 0 E

Series

Tolerance
F = 1%
H = 3%
J = 5%
K = 10%

Ohms
IR0 = 1 Ω
250 = 250 Ω
1K0 = 1,000 Ω
25K = 25,000 Ω
25K5 = 25,500 Ω

MADE-TO-ORDER PARTS

See web-site for custom color info	Non-Inductive Winding Optional (blank = std. winding)	Core Diameter See "Core and Terminal Selection"	RoHS Compliant	
	2 0 0 0 N 8 D 5 R 0 0 0 J E			
	Coating 200 = Vitreous 400 = Silicone Ceramic	Wattage 3 5.25 8 12 20	Ohms R500 = 0.500 Ω 1R00 = 1 Ω 250R = 250 Ω 1K00 = 1,000 Ω 25K0 = 25,000 Ω 25K5 = 25,500 Ω	Tolerance F = 1% H = 3% J = 5% K = 10%

STANDARD PART NUMBERS FOR 200 SERIES

Wattage						Wattage						Wattage						Wattage						Wattage					
Ohmic value	Part No.	5.25	8	12	20	Ohmic value	Part No.	5.25	8	12	20	Ohmic value	Part No.	5.25	8	12	20	Ohmic value	Part No.	5.25	8	12	20	Ohmic value	Part No.	5.25	8	12	20
	Prefix Suffix						Prefix Suffix						Prefix Suffix						Prefix Suffix						Prefix Suffix				
0.5	R50E					20	20RE					270	270E	✓				2,250	2K25E	✓	✓			16,000	16KE				
1	1R0E	✓	✓	✓	✓	22	22RE	✓				300	300E		✓	✓	✓	2,400	2K4E					17,500	17K5E	✓	✓		
1.1	1R1E					24	24RE	✓				330	330E	✓				2,500	2K5E			✓	✓	18,000	18KE		✓	✓	
1.2	1R2E					25	25RE		✓	✓	✓	350	350E				✓	2,700	2K7E	✓				20,000	20KE	✓	✓	✓	✓
1.3	1R3E					27	27RE	✓				360	360E					2,750	2K75E				✓	22,500	22K5E		✓		
1.5	1R5E	✓	✓	✓		30	30RE		✓	✓	✓	390	390E	✓				3,000	3K0E	✓	✓	✓	✓	25,000	25KE		✓	✓	✓
1.6	1R6E	✓				33	33RE	✓				400	400E		✓	✓	✓	3,300	3K3E	✓				30,000	30KE		✓	✓	✓
1.8	1R8E					35	35RE			✓	✓	430	430E					3,500	3K5E		✓	✓	✓	35,000	35KE		✓	✓	✓
2	2R0E	✓	✓		✓	36	36RE					450	450E		✓	✓		3,600	3K6E					40,000	40KE		✓	✓	✓
2.2	2R2E					39	39RE	✓				470	470E	✓				3,900	3K9E	✓				45,000	45KE		✓		
2.4	2R4E	✓				40	40RE			✓	✓	500	500E		✓	✓	✓	4,000	4K0E		✓	✓	✓	50,000	50KE		✓	✓	
2.7	2R7E	✓				43	43RE	✓				510	510E	✓				4,300	4K3E					55,000	55KE				
3	3R0E		✓	✓	✓	47	47RE					560	560E	✓				4,500	4K5E	✓	✓	✓		60,000	60KE				
3.3	3R3E	✓				50	50RE		✓	✓	✓	600	600E		✓	✓		4,700	4K7E	✓	✓			65,000	65KE				
3.6	3R6E	✓				51	51RE	✓				620	620E	✓				5,000	5K0E		✓	✓	✓	70,000	70KE				
3.9	3R9E	✓				56	56RE					650	650E				✓	5,100	5K1E	✓				75,000	75KE				
4	4R0E		✓	✓	✓	62	62RE	✓				680	680E	✓				5,600	5K6E					80,000	80KE				✓
4.3	4R3E					68	68RE					700	700E			✓	✓	6,000	6K0E		✓	✓	✓	85,000	85KE				
4.7	4R7E	✓				75	75RE		✓	✓	✓	750	750E	✓	✓	✓	✓	6,200	6K2E	✓				90,000	90KE				
5	5R0E		✓	✓	✓	82	82RE	✓				800	800E		✓	✓	✓	6,800	6K8E	✓				95,000	95KE				
5.1	5R1E	✓				91	91RE	✓				820	820E	✓				7,000	7K0E		✓	✓	✓	100,000 — 100KE ✓ = Standard values; check availability using the world- wide inventory search at www.ohmite.com					
5.6	5R6E	✓				100	100E	✓	✓	✓	✓	900	900E		✓	✓		7,500	7K5E		✓	✓	✓						
6.2	6R2E	✓				110	110E					910	910E					8,000	8K0E		✓	✓	✓						
6.8	6R8E	✓				120	120E					1,000	1K0E	✓	✓	✓	✓	8,200	8K2E	✓									
7.5	7R5E	✓	✓	✓		125	125E		✓	✓	✓	1,100	1K1E	✓	✓			8,500	8K5E										
8.2	8R2E	✓				130	130E			✓		1,200	1K2E	✓		✓	✓	9,000	9K0E		✓		✓	These values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling: B5: 6.8K-20KΩ B8: 12.5K-25KΩ B12: 30K-51KΩ B20: 22.5K-100KΩ					
9.1	9R1E	✓				150	150E	✓	✓		✓	1,250	1K25E		✓	✓	✓	9,100	9K1E										
10	10RE		✓	✓	✓	160	160E					1,300	1K3E	✓				10,000	10KE		✓	✓	✓						
11	11RE					180	180E	✓				1,500	1K5E	✓	✓	✓	✓	11,000	11KE										
12	12RE	✓	✓	✓		200	200E	✓	✓	✓	✓	1,600	1K6E					12,000	12KE		✓								
13	13RE					220	220E	✓				1,750	1K75E		✓	✓	✓	12,500	12K5E		✓	✓	✓						
15	15RE	✓	✓	✓		225	225E			✓		1,800	1K8E					13,000	13KE	✓									
16	16RE					240	240E	✓				2,000	2K0E	✓	✓	✓	✓	13,500	13K5E				✓						
18	18RE					250	250E		✓	✓	✓	2,200	2K2E	✓				15,000	15KE	✓	✓	✓	✓						