

**Si4427DY****New Product****Vishay Siliconix****P-Channel 30-V (D-S) MOSFET****PRODUCT SUMMARY**



V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
-30	0.0105 @ $V_{GS} = -10$ V	-13.3
	0.0125 @ $V_{GS} = -4.5$ V	-12.2
	0.0195 @ $V_{GS} = -2.5$ V	-9.8

FEATURES

- TrenchFET® Power MOSFETs

**RoHS**
COMPLIANT

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Ordering Information: Si4427DY-T1
Si4427DY-T1-E3 (Lead (Pb)-free)

P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter		Symbol	10 secs	Steady State	Unit
Drain-Source Voltage		V _{DS}	−30		V
Gate-Source Voltage		V _{GS}	± 12		
Continuous Drain Current (T _J = 150°C) ^a	T _A = 25°C	I _D	−13.3	−9.4	A
	T _A = 70°C		−10.7	−7.5	
Pulsed Drain Current		I _{DM}	−50		
continuous Source Current (Diode Conduction) ^a		I _S	−2.5	−1.3	
Maximum Power Dissipation ^a	T _A = 25°C	P _D	3.0	1.5	W
	T _A = 70°C		1.9	0.9	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	−55 to 150		°C

THERMAL RESISTANCE RATINGS

Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^a	$t \leq 10$ sec	R_{thJA}	32	42	$^\circ\text{C/W}$
	Steady State		68	85	
Maximum Junction-to-Foot (Drain)	Steady State	R_{thJF}	15	18	

Notes

a. Surface Mounted on 1" x 1" FR4 Board.

Si4427DY**Vishay Siliconix**



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)







**SPECIFICATIONS ($T_J = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)**

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\ \mu\text{A}$	-0.60		-1.7	V
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\ \text{V}, V_{GS} = \pm 12\ \text{V}$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -30\ \text{V}, V_{GS} = 0\ \text{V}$			-1	μA
		$V_{DS} = -30\ \text{V}, V_{GS} = 0\ \text{V}, T_J = 55^\circ\text{C}$			-5	
On-State Drain Current ^a	$I_{D(on)}$	$V_{DS} \leq -5\ \text{V}, V_{GS} = -10\ \text{V}$	-50			A
Drain-Source On-State Resistance ^a	$r_{DS(on)}$	$V_{GS} = -10\ \text{V}, I_D = -13.3\ \text{A}$		0.0086	0.0105	Ω
		$V_{GS} = -4.5\ \text{V}, I_D = -12.2\ \text{A}$		0.0105	0.0125	
		$V_{GS} = -2.5\ \text{V}, I_D = -9.8\ \text{A}$		0.0165	0.0195	
Forward Transconductance ^a	g_{fs}	$V_{DS} = -15\ \text{V}, I_D = -13.3\ \text{A}$		40		S
Diode Forward Voltage ^a	V_{SD}	$I_S = -2.5\ \text{A}, V_{GS} = 0\ \text{V}$		-0.8	-1.2	V
Dynamic^b						
Total Gate Charge	Q_g	$V_{DS} = -15\ \text{V}, V_{GS} = -4.5\ \text{V}, I_D = -13.3\ \text{A}$		47	70	nC
Gate-Source Charge	Q_{gs}			20		
Gate-Drain Charge	Q_{gd}			8.3		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = -15\ \text{V}, R_L = 15\ \Omega$ $I_D \cong -1\ \text{A}, V_{GEN} = -10\ \text{V}, R_G = 6\ \Omega$		16	25	ns
Rise Time	t_r			12	20	
Turn-Off Delay Time	$t_{d(off)}$			220	330	
Fall Time	t_f			70	110	
Source-Drain Reverse Recovery Time	t_{rr}	$I_F = -2.5\ \text{A}, di/dt = 100\ \text{A}/\mu\text{s}$		50	80	





Notes

- a. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$.
 b. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

**TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)****On-Resistance vs. Drain Current****Capacitance****Gate Charge****On-Resistance vs. Junction Temperature****Source-Drain Diode Forward Voltage****On-Resistance vs. Gate-to-Source Voltage**

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)