

4K nMOS Static RAM (1024×4) 18PIN 2114

型 名	社 名	温度範囲 (℃)	スイッチング 特性										電 源		入 力 [*typ]			出 力 [*typ]			備 考	
			TAAC max (ns)	TCAC max (ns)	TDE max (ns)	TOH min (ns)	TOD max (ns)	TWP min (ns)	TDS min (ns)	TDH min (ns)	TWD min (ns)	TWR max (ns)	VDD or VCC (V)	IDO max (mA)	IDD STANDBY (1SB/1SB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/I VOL max (V/mA)	VOH/I VOH min (V/mA)		Co max (pF)
TMS314AP	TOSHIBA	0~70	450			20	100	200	200	0	30	0	4.5~5.5	100		0.8	2.0	5	0.4/2.1	2.4/1.0	5	
TMS314AP-1	TOSHIBA	0~70	200			20	40	120	120	0	30	0	4.5~5.5	100		0.8	2.0	5	0.4/2.1	2.4/1.0	5	
TMS314AP-3	TOSHIBA	0~70	300	100		20	80	150	150	0	0	0	4.5~5.5	90		0.8	2	5	0.4/2.1	2.4/1	5	
TMS314APL	TOSHIBA	0~70	450			20	100	200	200	0	30	0	4.5~5.5	70		0.8	2.0	5	0.4/2.1	2.4/1.0	5	
TMS314APL-1	TOSHIBA	0~70	200			20	40	120	120	0	30	0	4.5~5.5	70		0.8	2.0	5	0.4/2.1	2.4/1.0	5	
TMS314APL-3	TOSHIBA	0~70	300	100		20	80	150	150	0	0	0	4.5~5.5	64		0.8	2	5	0.4/2.1	2.4/1	5	
TMS2114AP-12	TOSHIBA	0~70	120	70	15	20	35	70	70	0	0	0	4.5~5.5	60		0.8	2	5	0.4/2.1	2.4/1	10	
TMS2114AP-15	TOSHIBA	0~70	150	70	15	20	40	90	90	0	0	0	4.5~5.5	60		0.8	2	5	0.4/2.1	2.4/1	10	
TMS40L45-25	TI	0~70	200	100			40	100	100	0	0	20	4.5~5.5	70				8	0.4/2	2.4/0.2	12	STAND BY MODE
TMS40L45-30	TI	0~70	300	100			80	150	150	0	0	20	4.5~5.5	70				8	0.4/2	2.4/0.2	12	STAND BY MODE
TMS40L45-45	TI	0~70	450	120			100	200	200	0	0	20	4.5~5.5	70				8	0.4/2	2.4/0.2	12	STAND BY MODE
TMS2114-15	TI	0~70	150	70	20	20	50	80	80	0	0	0	4.5~5.5	100		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114-20	TI	0~70	200	85	0	20	60	100	100	0	0	0	4.5~5.5	100		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114-25	TI	0~70	250	100	15	20	60	100	100	0	0	0	4.5~5.5	100		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114-45	TI	0~70	450	120	15	20	100	200	200	0	0	20	4.75~5.25	100		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114L-15	TI	0~70	150	70	15	20	50	80	80	0	0	0	4.5~5.5	60		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114L-20	TI	0~70	200	85	15	20	60	100	100	0	0	0	4.5~5.5	60		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114L-25	TI	0~70	250	100	15	20	60	100	100	0	0	0	4.5~5.5	60		0.8	2	8	0.4/3.2	2.4/1	8	
TMS2114L-45	TI	0~70	450	120	15	20	100	200	200	0	0	20	4.75~5.25	60		0.8	2	8	0.4/3.2	2.4/1	8	
TMS4045-20	TI	0~70	200	70		10	40	75	75	0	0		4.5~5.5	80		0.8	2	8	0.4/2	2.2/2	12	
TMS4045-30	TI	0~70	300	100		10	80	150	150	0	0		4.5~5.5	80		0.8	2	8	0.4/2	2.2/2	12	
TMS4045-45	TI	0~70	450	100		10	100	200	200	0	0		4.5~5.5	80		0.8	2	8	0.4/2	2.2/2	12	
uPD2114LC/D	NEC	0~70	450	120	20	50	100	200	200	0	0	0	4.5~5.5	70		0.8	2	5	0.4/3.2	2.2/1	12	
uPD2114LC/D-1	NEC	0~70	300	100	20	50	80	150	150	0	0	0	4.5~5.5	70		0.8	2	5	0.4/3.2	2.2/1	12	
uPD2114LC/D-2	NEC	0~70	250	80	20	50	70	120	120	0	0	0	4.5~5.5	70		0.8	2	5	0.4/3.2	2.2/1	12	
uPD2114LC/D-3	NEC	0~70	200	70	20	50	60	120	120	0	0	0	4.5~5.5	70		0.8	2	5	0.4/3.2	2.2/1	12	
uPD2114LC/D-5	NEC	0~70	150	60	20	50	50	80	80	0	0	0	4.5~5.5	70		0.8	2	5	0.4/3.2	2.2/1	12	
uPD2149D	NEC	0~70	55	25		5	20	40	20	5	0	5	4.5~5.5	180		0.65	2.2	7	0.4/8	2.4/4	5	
uPD2149D-1	NEC	0~70	45	20		5	15	35	20	5	0	5	4.5~5.5	180		0.65	2.2	7	0.4/8	2.4/4	5	
uPD2149D-2	NEC	0~70	35	15		5	10	30	20	5	0	5	4.5~5.5	180		0.65	2.2	7	0.4/8	2.4/4	5	

勝 特 力 材 料 886-3-5753170

胜特力电子(上海) 86-21-54151736

胜特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw