

塑膠齒輪油膏

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

EG 503 is special plastic grease with excellent long-term lubrication, EP & Anti-wear Properties, plastics compatibility, developed for use in electronic devices, offices appliance equipments, optical equipments. This product is compatible with plastics and giving no harm to electrical contacts.

FEATUREES

- 1.Lifetime lubrication of steel/steel, steel/plastic and plastic/plastic
- 2.Has a wide service temperature range from -50 to 150⁰C
- 3.Excellent EP & Abrasion prevention
- 4.Compatible with metals and most plastics

APPLICATION

Best suitable for lubrication of electric, electronic and automotive components applications such as in VCR, audio equipment, automotive small motors

PROPERTIES

Appearance	white
NLGI No.	1
Worked Penetration (25 ⁰ C)	310-340
Dropping Point (⁰ C)	205
Oil Separation (wt %)	4
Copper corrosion	passed
Oxidation Stability (kg/cm ²)	0.15
Low temp torque (-30 ⁰ C, gf·cm)	
Starting	290
Running	140
Polystyrene foam test	no change
Base Oil	Synthetic oil
Thickener	Lithium-soap

* These values are not intended for use in preparing specifications.

USAGE

The surface of the material to be applied must be cleaned and dried, apply by brushing, dispense machine. To mix well before use is recommended.

PACKAGING

1kg x 10 containers / 3.6kg containers