

Soldering Tips

for WSP80, WP80 and MPR80



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



WSP80 (page 11)



WP80 (page 10)



MPR80 (page 11)

Type	Description	Width A	Thickness B	Length	Order No.
LT 1L	Conical long	Ø 0.2mm		26.4mm	LT1L
LT S	Conical long	Ø 0.4mm		21.0mm	LTS
LT 1LX	Conical long bent	Ø 0.2mm		26.4mm	LT1LX
LT GW	Gull wing 45°	Ø 2.3mm	3.2mm	18.8mm	LTGW
LT KN	Knife tip	6.2mm		16.0mm	LTKN
Type K Thermocouple Assembly	Type K Thermocouple Assembly	2.4mm	0.8mm	13.5mm	K181
Type K Thermocouple Assembly for WP80	Type K Thermocouple Assembly for WP80	2.4mm	0.8mm	13.5mm	K1111

All Weller "Longlife" tips are designed for working with leadfree application

Use only Weller® soldering tips. The use of non-Weller® components may void product warranty if the non-Weller® component causes damage to the unit.

SMT soldering tip for reworks on SMT components

Type	Description	Width A	Thickness B	Length C	Order No.
LT SMT01	Blade	10.4mm	0.6mm	7.1mm	LTSMT01
LT SMT02	Blade	16.8mm	0.6mm	7.1mm	LTSMT02
LT SMT03	Blade	20.8mm	0.6mm	7.1mm	LTSMT03