



Features

- Semi-shielded construction
- Miniature size
- Low profile - 1.0 mm max.
- Inductance range: 1 to 47 μ H
- Rated current up to 2.3 A
- RoHS compliant* and halogen free**

Applications


- DC/DC converters
- Notebook computers
- Digital video cameras
- HDDs
- Cell phones
- Televisions, LCD displays

SRN3010 Series - Semi-shielded Power Inductors


Electrical Specifications @ 25 °C

Bourns Part No.	Inductance @ 100 KHz / 1 V		DCR (Ω) Max.	Irms (A)	Isat (A)
	L (μ H)	Tol. %			
SRN3010-1R0Y	1.0	30	0.063	2.3	2.3
SRN3010-1R2Y	1.2	30	0.081	2.1	1.9
SRN3010-1R5Y	1.5	30	0.091	2.0	1.65
SRN3010-2R2M	2.2	20	0.096	1.9	1.3
SRN3010-3R3M	3.3	20	0.156	1.8	1.05
SRN3010-4R7M	4.7	20	0.210	1.7	0.85
SRN3010-6R8M	6.8	20	0.312	1.3	0.7
SRN3010-100M	10	20	0.420	0.9	0.6
SRN3010-150M	15	20	0.612	0.8	0.5
SRN3010-220M	22	20	0.936	0.7	0.4
SRN3010-330M	33	20	1.320	0.5	0.32
SRN3010-470M	47	20	1.920	0.35	0.28


Soldering Profile



Electrical Schematic



Recommended Layout



General Specifications

Operating Temperature -40 °C to +125 °C
(Temperature rise included)
Storage Temperature .. -25 °C to +120 °C
Resistance to Solder Heat +260 °C for 10 sec.
Temperature Rise 40 °C at rated Irms
Rated Current Inductance drops 30 % at Isat




Materials

Core Ferrite
Wire Enameled copper
Terminal Finish Sn
Coating Magnetic epoxy resin
Packaging 2000 pcs. per 7-inch reel

How to Order

Model SRN3010 - 100M
Value Code (see table)

Product Dimensions



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

* RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

** Bourns follows the prevailing definition of "halogen free" in the industry. Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

