

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>



PRODUCT-DETAILS

CA5-40E

CA5-40E Auxiliary Contact Block



General Information	
Extended Product Type:	CA5-40E
Product ID:	1SBN010040R1040
EAN:	3471522121080
Catalog Description:	CA5-40E Auxiliary Contact Block
Long Description:	CA5-40E is a 4-pole front mounted auxiliary contact block equipped with screw terminals. CA5-..E version offers terminal assortment matching the marking of 3-pole A serie contactors: A..-30-00, A..-40-00, A..-22-00. CA5-40E is available with 4 N.O. and 0 N.C. instantaneous contacts for standard industrial environments.
Display Name:	CA5-40E

Ordering	
Minimum Order Quantity:	2 piece
Customs Tariff Number:	85389099

Popular Downloads

Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101012M5501
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	43 mm
Product Net Depth / Length:	39 mm
Product Net Height:	47 mm
Product Net Weight:	0.06 kg

Technical

Number of Auxiliary Contacts NO:	4
Number of Auxiliary Contacts NC:	0
Number of Poles:	4P
Rated Operational Voltage:	Auxiliary Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I_e):	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Rated Operational Current DC-13 (I_e):	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Short-Circuit Protective Devices:	Auxiliary Circuit - gG Type Fuses 10 A
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 0.1 s 140 A for 1 s 100 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Maximum Electrical Switching Frequency:	1200 cycles per hour
Mechanical Durability:	10 million 3 million
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Minimum Switching Capacity:	A9 ... A75 17 / 5 VLT4K A95 ... A110 24 / 50 VLT4K
Power Loss:	at Rated Operating Conditions per Pole 0.1 W
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Terminal Type:	Screw Terminals

Suitable For:	AF45
	AF50
	AF63
	AF75
	AF95B
	GAF75
	A9
	A16
	A26
	A45
	A50
	A63
	A75
	A95
	A110
	AL9
	AL16
	AL26
	AE45
	AE50
	AE63
	AE75
	TAL9
	TAL16
	TAL26
	TAE45
	TAE50
	TAE75
	GA75
	GAE75
	UA50
	UA63
	UA75
	UA95
	UA110
Product Name:	Auxiliary Contact Block
Remarks:	100

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

Environmental Product Declaration - EPD:	No declaration needed
--	-----------------------

Certificates and Declarations

CB Certificate:	CB_SE_62119A1
-----------------	---------------

CCC Certificate:	CCC_2015010304800518
CQC Certificate:	CQC2015010304800518 CQC2004010305133985
Declaration of Conformity - CCC:	2020980304001627 2020980305001185
Declaration of Conformity - CE:	1SBD250809U1000
Declaration of Conformity - UKCA:	1SBD250826U1000
DNV GL Certificate:	DNV_GL_TAE00001UT
RINA Certificate:	RINA_ELE172319XG001
UL Certificate:	UL_071301E48139

Container Information

Package Level 1 Units:	box 2 piece
Package Level 1 Width:	65 mm
Package Level 1 Depth / Length:	129.5 mm
Package Level 1 Height:	43 mm
Package Level 1 Gross Weight:	0.12 kg
Package Level 1 EAN:	3471522121080

External Classifications and Standards

Object Classification Code:	K
ETIM 7:	EC000041 - Auxiliary contact block
ETIM 8:	EC000041 - Auxiliary contact block
ETIM 9:	EC000041 - Auxiliary contact block
eClass:	V11.0 : 27371302
UNSPSC:	39121522
IDEA Granular Category Code (IGCC):	4743 >> Auxiliary contact block
E-Number (Finland):	3709195

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力電子(上海) 86-21-34970699
勝特力電子(深圳) 86-755-83298787
<http://www.100y.com.tw>