

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Main

| | |
|--|--|
| Range of product | TeSys D thermal overload relays |
| Product or component type | Non differential thermal overload relay |
| Device short name | LR3D |
| Relay application | Motor protection |
| Product compatibility | LC1D09...LC1D38 |
| Network type | AC DC |
| Overload tripping class | Class 10A conforming to IEC 60947-4-1 |
| Thermal protection adjustment range | 4...6 A |
| [U _i] rated insulation voltage | 690 V power circuit conforming to IEC 60947-4-1 600 V power circuit conforming to UL 600 V power circuit conforming to CSA |

Complementary

| | |
|--|---|
| Network frequency | 0...400 Hz |
| Mounting support | Under contactor |
| Tripping threshold | 1.14 +/- 0.06 I _r conforming to IEC 60947-4-1 |
| [I _{th}] conventional free air thermal current | 5 A for signalling circuit |
| Permissible current | 0.22 A at 125 V DC-13 for signalling circuit 3 A at 120 V AC-15 for signalling circuit |
| [U _e] rated operational voltage | 690 V AC 0...400 Hz |
| [U _{imp}] rated impulse withstand voltage | 6 kV |
| Phase failure sensitivity | Tripping current 130 % of I _r on two phase, the last one at 0 |
| Temperature compensation | -30...60 °C |
| Connections - terminals | Power circuit: screw clamp terminals 1 cable(s) 1...6 mm ² - cable stiffness: solid - without cable end Power circuit: screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm ² - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - without cable end |
| Tightening torque | Power circuit: 1.7 N.m - on screw clamp terminals Control circuit: 1.7 N.m - on screw clamp terminals |
| Width | 45 mm |
| Depth | 70 mm |
| Product weight | 0.124 kg |
| Quantity per set | Set of 10 |

Environment

| | |
|---------------------------------------|---|
| Standards | EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Product certifications | ATEX INERIS BV CCC CSA DNV GL GOST RINA UL LROS |
| Protective treatment | TH conforming to IEC 60068 |
| IP degree of protection | IP2x conforming to VDE 0106 |
| Ambient air temperature for operation | -20...60 °C without derating conforming to IEC 60947-4-1 |
| Ambient air temperature for storage | -60...70 °C |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Shocks 15 Gn for 11 ms IEC 60068-2-7 Vibrations 6 Gn IEC 60068-2-6 |
| Dielectric strength | 6 kV at 50 Hz conforming to 60255-5 |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)