

## SCSI External Cables



### DESCRIPTION

Multi-platform SCSI II external peripheral cable HD50M to C50M. This 6ft cable is designed to connect two SCSI II (fast SCSI) devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

### KEY BUYING POINTS

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

### OPTIONS & ACCESSORIES

- Additional External SCSI Adapters include: HD50M/C50F: (#S232-000), HD68M/HD50F: (#S244-000)
- External SCSI Cable Options: HD50M/C50M (#S356-006), HD68M/C50M (S432-006)
- External Terminator Options: HD50 Active (#S122-000), C50 Active: (#S112-000), HD68 Active: (#S132-000)

### SYSTEM REQUIREMENTS

- Any external SCSI II device or controller card requiring Cen50 or HD50 interface

### PACKAGE INCLUDES

- 6-ft. SCSI cable HD50M to centronic 50M double shielded

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)


### COMPLETE SPECIFICATIONS

**Description** SCSI II Cable HD50M/C50M - 6'

**Length** 6 ft.


#### CONNECTORS

**Connector A**



HD50 (Male)

**Connector B**



Centronics 50 (Male)