

## Wireless Thermometer

DE-31



DE-31

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### FEATURES :

- RF Transmission
- Remote Monitoring Temperature Change
- Dual Display Of Temperature From Two Positions
- Auto Refresh Data (3 minutes from sensor unit & 10 seconds on main unit)
- Alarm Mode For HI or LO Temperature Set
- Auto Data Logger
- Max/Min Temperature Memory With Time Indication
- 24 Hours Clock Indication
- Indoor & Outdoor Use

### SPECIFICATIONS:

- RF transmission range:** wireless transmission of data-distance 1000 feet (300M) at open space
- RF transmission frequency:** approx. 433.92MHz
- Interval of transmission from sensor to main unit :** 3 minutes
- Temperature Range:** -20°C ~ 50°C (-4°F ~ 122°F)
- Accuracy:** ± 1.0°C ( ± 2.0°F)
- 24 sets auto data logger every 30 minutes
- Selectable HI or LO temperature range set
- Battery:** battery AAA x 2 each for main & sensor unit

### TEMP. / HUMIDITY:

- Operation:**
  - Temperature:**
    - Receiver (main unit): -20°C~50°C (-4°F~122°F)
    - Transmitter (sensor unit): -20°C~50°C (-4°F~122°F)
    - \* extension temp. probe: -30°C~70°C (-22°F~158°F)
  - Humidity:** <80% R.H. (no condensation)
- Storage:** -30°C~60°C (-22°F ~140°F)  
 <70% R.H. (no condensation)

### DIMENSION & WEIGHT:

- Main unit:** 120(L) x 100(W) x 26(H) mm ( 4.72" x 3.94" x1" ), approx. 180g (0.40 lbs)
- Sensor unit:** 92(L) x 70(W) x 26(H) mm ( 3.62" x 2.76" x1" ), approx. 100g (0.22 lbs)

### ACCESSORIES:

- Battery AAA 1.5V ..... 4
- Instruction manual ..... 1
- Extension temperature probe (2M) ..... 1
- Suction Cap ..... 1