

DT-2289

STROBOSCOPE + photo tachometer, 2 in 1, XENON

閃光同步儀+光電式轉速計



Description :

勝特力材料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- * Stroboscope use high intensity XENON tube.
- * LCD display with back light.
- * Stroboscope range : 100 to 15,000 RPM.
- * External trigger for stroboscope.
- * Photo tach. range : 10 to 99,999 RPM.
- * Photo tachometer use the laser light beam.
- * Optional contact tach. adapter, TA-35.
- * DCV power supply via external AC/DC adapter, 90-260 ACV/DC adapter is the standard accessory.
- * Build in battery compartment, power can use the DC 1.2 V Ni-MH recharge battery (UM-1, D size, BAUM-01) X 4 PCs, the recharger batteries and the battery charger (BACH-220/220 ACV, BACH-110/110ACV) are the optional accessories.

- * 測量範圍：閃頻：100~1500RPM ($\pm 0.05\%$).
光電：10~99999RPM ($\pm 0.05\%$).
- * 閃頻採用高亮度氙光燈管.
- * 液晶顯示器，具有背光顯示功能.
- * 外部觸發信號輸入功能.
- * 光電式轉速測量，採用紅色雷射光投射.
- * 工作電源：1 號電池 x4 或 DC9 伏特.(Adapter)
- * Size : 210x120x120mm