

hybrid power, Patent

GREEN POWER SOUND LEVEL METER

Model : SL-4113G

ISO-9001, CE, IEC1010



No battery
GGenerator power



- 測量範圍：30dB ~ 130dB (分貝).
- 測量頻率範圍：31.5 ~ 8000Hz
- 符合國際規範IEC651Type2
- A/C頻率加權及時間加權選擇'快&慢'選擇
- 採分離式麥克風設計, 可延伸2米長
- 自動換檔及手動換檔選擇
- 峰值鎖定及記錄測量中之最大/最小值
- RS-232 / USB 連接介面及AC電軌信號輸出
- Size: 195 x 68 x 30mm.

GREEN POWER SOUND LEVEL METER

Model : SL-4113G

FEATURES

- * Hybrid power, power supply from green power (handy generator) or battery. If power source come from " Green power ", battery is no need. Operate the generator 30 seconds will offer several minutes energy typically.
- * Main functions are designed to meet IEC 61672 class 2.
- * A & C weighting networks comply with standards.
- * 0.5" standard microphone head.
- * Time weighting (Fast & Slow) dynamic characteristic modes.
- * RS232/USB computer interface.
- * Auto range & Manual range selection.
- * Available for external calibration adjustment.
- * Condenser microphone for high accuracy & long-term stability.
- * Memory function to store the Max. & Min. value.
- * Hold and Peak Hold functions.
- * Operation key used push button.
- * LCD display for low power consumption & clear read-out even in bright ambient light condition.
- * Using the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
- * Small and light weight design allow one hand operation.

SPECIFICATIONS

Display	40 mm x 32 mm LCD (Liquid crystal display).
Function	dB (A & C frequency weighting), Time weighting (Fast, Slow), Hold, Memory (Max. & Min.), Peak hold, RS232 output.
Measurement Range	30 - 130 dB.
Resolution	0.1 dB.
Accuracy (23± 5 °C)	* Meet IEC 61672 class 2, tested under Input signal level on 94 dB & frequency range from 31.5 Hz to 8 k Hz, refer to page 12.
Range selector	<i>Auto range :</i> 30 to 130 dB. <i>Manual range :</i> 3 range, 30 to 80 dB, 50 to 100 dB, 80 to 130 dB, 50 dB on each step, with over & under range indicating.
Frequency	31.5 to 8,000 Hz.
Microphone type	Electric condenser microphone.
Microphone size	Out size, 12.7 mm DIA. (0.5 inch).
Weighting Network	Characteristics of A & C.

* Appearance and specifications listed in this brochure are subject to change without notice.

Time weighting (Fast & Slow)	Fast - t = 200 ms, Slow - t = 500 ms, * "Fast" range is simulated the human ear response time. * "Slow" range is easy to get the avg. values of vibration sound level. * The "Fast" & "Slow" response range are designed to meet IEC 61672 class 2 requirement.
Calibrator	B & K (Bruel & kjaer), MULTIFUNCTION ACOUSTIC CALIBRATOR 4226.
Output Signal	Serial data interface.
Output terminal	* Connect the optional RS232 cable UPCB-02 will get the RS232 plug (D9 plug).. * Connect the optional USB cable USB-01 will get the USB plug. <i>Terminal socket size :</i> 3.5 mm dia. phone socket.
Calibration VR	Build in external calibration VR, easy to calibrate on 94 dB level by screw driver.
Operating Temp.	0 to 50 °C (32 to 122 °F).
Operating Humidity	Less than 80% RH.
Power Supply * Hybrid power	Green power : Power from the handy generator, battery is no need. Battery power : DC 9V battery, 006P, MN1604(PP3) or equivalent. * Alkaline or heavy duty type.
Power Consumption	Battery power : Approx. DC 10 mA.
Dimension	240 x 69 x 38 mm (9.4 x 2.7 x 1.1.5 inch).
Weight	390 g/0.86 LB (including battery).
Accessory Included	Instruction Manual 1 PC.
Optional Accessories	<i>94 dB Sound Calibrator :</i> Model : SC-941. <i>94 dB/114 dB Sound Calibrator :</i> Model : SC-942. <i>Sound wind shield ball</i> Model : SB-01 <i>RS232 cable (isolated RS232 cable) :</i> Model : UPCB-02. <i>USB cable</i> Model : USB-01 <i>Application windows software :</i> Model : SW-U801-WIN.

0801-SL4113G