

UV LIGHT METER

Model : SP-82UV

ISO-9001, CE, IEC1010

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Lutron

LUTRON ELECTRONIC

The Art of Measurement

UV LIGHT METER

Model : SP-82UV

FEATURES

* UV light measurement, calibration is executed under the UVA light & and compare with the standard UVA light meter.
* UV sensor structure The exclusive UV photo sensor with the cosine correction filter.
* UV sensor spectrum Band pass 250 nm to 390 nm.
* Tiny bone shape with light weight and small size case design are suitable for handling with one hand.
* Wristlet design provides extra protection to the instrument especially for user one hand operation.
* Built- in microprocessor circuit assures excellent performance and accuracy.
* Concise and compact buttons arrangement, easy operation.
* Memorize the maximum and minimum value with recall.
* Hold function to freeze the current reading value.

GENERAL SPECIFICATIONS

Display	8 mm LCD display
Measurement	UV Light
Operating Humidity	Max. 80% RH.
Operating Temperature	0 to 50 °C (32 to 122 °F)
Over Input Display	Indication of "- - - - "
Power Supply	CR 2032 DC 3V battery
Power Consumption	Approx. DC 5 mA
Weight	160g (battery included)
Dimension	HWD 120 x 45 x 20 mm (4.7 x 1.8 x 1.2 inch).
Standard Accessory	Instruction Manual

ELECTRICAL SPECIFICATION (23 ± 5°C)

UV Light * auto range * UVA light measurement		
Range	Resolution	Accuracy
0 to 1999 $\mu\text{W}/\text{cm}^2$	1 $\mu\text{W}/\text{cm}^2$	$\pm (4 \% \text{ FS} + 2 \text{ dgt})$
2 to 20.00 mW/cm^2	0.01 mW/cm^2	FS : full scale
Remark		
* Calibration is executed under the UVA light & and compare with the standard UVA light meter.		
* UV Sensor structure : The exclusive UV photo sensor with the cosine correction filter.		
* UV sensor spectrum Band pass 250 nm to 390 nm.		

UV Light sensor spectrum

