

TEMP. (type K) TRANSMITTER

Model : TR-TMK1A4

ISO-9001, CE, IEC1010



Temp. probe
Optional

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



LUTRON ELECTRONIC

The Art of Measurement

Temperature (type K)

TRANSMITTER

Model : TR-TMK1A4-500C

Model : TR-TMK1A4-100C

Measure Range	TR-TMK1A4-500C 0 to 500 °C	TR-TMK1A4-100C 0 to 100 °C
Output	4 - 20 mA	
	TR-TMK1A4-500C 0 °C = 4 mA 250 °C = 12 mA 500 °C = 20 mA	TR-TMK1A4-100C 0 °C = 4 mA 50 °C = 12 mA 100 °C = 20 mA
External Adjustment	ZERO VR SPAN VR	
Power Supply	90 - 260 ACV 50 Hz/60 Hz	
Operation Temperature	0 - 50 °C 32 - 122 °F	
Operation Humidity	Less than 80 %RH	
Accessory Included	Type K temperature probe is optional.	
Optional Accessories	Type K temperature probe : TP-01 TP-02A TP-03 TP-04	
Mounting Case	Din rail or Wall ABS plastic	
Others	Type K standard input socket	

* Appearance and specifications listed in this brochure are subject to change without notice.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)