


**Type K/J, Pt 100 Thermometer, IR Thermometer
Real Time Data Logger, 16,000 Data, RS232**

Muti-function THERMOMETER

Model : YK-2005TM

ISO-9001, CE, IEC1010



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

FEATURES

- * High capacity, 16,000 data logger no.
- * Real time data logger (record year, month, date, hour, minute, second).
- * Type K/J, Pt100 ohm, IR Thermometer
- * Max., Min., Data hold, zero adjust.
- * Optional probe :
 - Type K/J, PT 100 ohm, IR
- * RS-232 computer interface
- * DC 1.5V (UM3, AA) x 4 PCs or DC 9V adapter in.
- * Size : 203 x 76 x 38 mm.



LUTRON ELECTRONIC

The Art of Measurement

**3 in 1, Type K/J, Pt 100 ohm, Infrared Thermometer
Real time data logger, 16000 Data logger no., RS232**

THERMOMETER

Model : YK-2005TM

**勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)**

1. FEATURES

* 3 in 1, Thermocouple (Type K/J) thermometer, Pt 100 ohm thermometer + Infrared thermometer.
* 0.1 degree resolution for Pt 100 ohm & type K/J.
* Wide temperature measuring range.
* 4 wires PT 100 ohm probe input, 0.00385 alpha coefficient, meet DIN IEC 751, high precision.
* Offset adjustment.
* Fast humidity measuring response time.
* Real time data logger, build in clock (hour-min.-sec., year-month-date).
* Auto data record, 16,000 Data logger no.
* Wide sampling time adjustment range from two seconds to 8 hours 59 minutes 59 seconds.
* RS232 computer interface.
* Can default auto power off or manual power off.
* Multi function with easy operation
* Large LCD with multiple display.
* Data hold, record max. and min. reading.
* Microcomputer circuit provides special function & offer high accuracy.
* Power by UM3 (1.5 V) x 4 batteries or DC 9V adapter.
* RS232 PC serial interface.
* Separate probe, easy for operation of different measurement environment.

Power Supply * main instrument	DC 1.5 V battery (UM3) x 4 PCs, (Heavy duty type). DC 9V adapter input. @ AC/DC power adapter is optional.
Power Supply * clock module	DC 3V silver battery. Type : CR2032.
Power Current	Approx. DC 21.5 mA @ Main instrument. + Type K/J (Pt 100) probe
Weight	515 g/ 1.13 LB. @ Battery is included.
Dimension	203 x 76 x 38 mm
Accessories Included	Instruction manual.....1 PC Type K probe, TP-01.....1 PC DC 3V silver battery, CR2032..... 1 PC Carrying case..... 1 PC
Optional Accessories	* Type K thermocouple probe. TP-02A, TP-03, TP-04 * Pt 100 ohm probe, PT-100P * Infrared Probe, YK-200PIR * AC to DC 9V adapter. * RS232 cable/UPCB-02, USB cable/USB-01 * Data Acquisition software, SW-U801-WIN. * Data Logger software, SW-DL2005.

2-1 General Specifications

Circuit	Custom one-chip of microprocessor LSI circuit.
Display	LCD size : 58 mm x 34 mm.
Measurement	1. Thermocouple probe @ Thermocouple type K @ Thermocouple type J 2. Platinum Pt 100 ohm (0.00385 alpha coefficient, meet DIN IEC 751) 3. Infrared Thermometer
Display Unit	°C, °F.
Resolution	0.1 °C, 0.1 °F.
Sampling Time of Data Logger	2 sec to 8 hour 59 min. 59 sec. @ Auto datalogger
Temperature Compensation	Automatic temp. compensation for the type K/J thermometer and Infrared Thermometer.
Linear Compensation	Both for Type K/J. Pt 100 ohm and the IR thermometer.
Offset Adjustment	Available to adjust the zero drift value, adjustment by pushing button.
Probe Input Socket	Type K/J probe : Standard 2 pin thermocouple socket. Pt 100 and IR probe : Exclusive socket.
Over Indication	Show "----".
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.
Sampling Time of display	Approx. 1 second.
Power off	Auto shut off saves battery life or manual off by push button.
Data Output	RS 232 PC serial interface.
Operating Temperature	0 to 50 °C.
Operating Humidity	Less than 80% R.H.

2-2 Electrical Specifications (23±5 °C)

Type K/J thermometer			
Sensor Type	Resolution	Range	Accuracy
Type K	0.1 °C	-50.0 to 1300.0 °C	± (0.2 % + 0.5 °C)
		-50.1 to -100.0 °C	± (0.2 % + 1 °C)
	0.1 °F	-58.0 to 2372.0 °F	± (0.2 % + 1 °F)
Type J		-58.1 to -148.0 °F	± (0.2 % + 1.8 °F)
	0.1 °C	-100.0 to 1100.0 °C	± (0.2 % + 0.5 °C)
		-50.1 to -100.0 °C	± (0.2 % + 1 °C)
	0.1 °F	-58.0 to 2012.0 °F	± (0.2 % + 1 °F)
		-58.1 to -148.0 °F	± (0.2 % + 1.8 °F)

* Accuracy value is specified for the meter only.
* Type K probe, TP-01 is the standard accessory.
* Other Type K probe. TP-02A, TP-03. TP-04 is the optional accessories.

Platinum PT 100 ohm Thermometer		
Resolution	Range	Accuracy
0.1 °C	-200.0 to 850.0 °C	± (0.2 % + 0.5 °C)
0.1 °F	-328.0 to 1562.0 °F	± (0.2 % + 1.0 °F)

Remark :

- Accuracy value is specified for the meter only.
- Linearity Correction :
Memorize the Pt 100 ohm's curve into the intelligent CPU circuit.
- Pt 100 probe input, 0.00385 alpha coefficient, meet DIN IEC 751.
- 4 wires Pt 100 ohm probe (Model : PT-100P) is optional.

Infrared Thermometer	
Measurement Range	-10 °C to 300 °C / 14 °F to 572 °F.
Resolution/ Accuracy	1°C or 1°F. ± 3 % of reading or ± 3°C which ever is greater. * It should cooperate the optional IR probe, YK-200PIR. * Meter operating Temp. within 23±5 °C & the emissivity value of measurement target is 0.95. * Spec. tested under the 20 cm dia. black body, the measuring distance from the Probe sensing Head is 30 cm.

* Appearance and specifications listed in this brochure are subject to change without notice.

0904-YK2005TM