

ST-303 ... 4 Channels Datalogger

勝 特 力 材 料 886-3-5753170
 胜特力电子(上海) 86-21-54151736
 胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- Sensors:External
- Type:Voltage/Current/Thermistor
- Channel(s) : 4
- Range :0~10V
- Accuracy: +/- (1% of reading+0.1V)
- Range : 4~20mA
- Accuracy:+/- (1% of reading+0.1mA)
- Range-80 to 150°C
- Accuracy: +/- 0.5°C at 20°C
- Resolution : 12bits
- Memory:256K
- Interface:USB
- Datalogger Storage: 60,000(20.000*4)
- Dimensions :61*47*15

Model	ST-301	ST-302	ST-303
Type	Temperature	Temp/Humidity	Voltage/ Current/Thermis
Channels	1	2	4
Range	-20°C to 70°C	-40°C to 85°C	0~10V
Accuracy	+/- 0.7°C at 21°C +/- 1.27°F at 70°F	+/- 0.7°C@25°C	+/-10mV +/- 1%
Range	NA	0-100% RH	4~20mA
Accuracy	NA	2.5% RH(10-90%Rh)	+/- 0.1mA +/-1%
Range	NA	NA	Thermistor
Accuracy	NA	NA	+/- 0.7°C at 21° +/- 1.27°F at 70
Resolution	12 Bits	12 Bits	12 Bits
Memory	64K	128K	256K
Interface	Serial/RS232	Serial/RS232	Serial/RS232
Datalogger Storage	30,000	Total:60,000 (30,000*2)	Total:60,000 (15,000*5)
Sensor	Internal	Internal	External