

TM-202 Digital Light Meter

DISPLAY

- 3½ digits LCD with maximum reading 2000.
- Overload indication.
- Low battery indication.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



FUNCTIONS

- According to JISC1609:1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in unit of Lux or Foot-candle.
- Measuring lights source include all visible range.
- Length of wire for light sensor: approximately 1.5M.
- Cosine angular corrected.



Model	TM-201	TM-202
Data hold	√	√
DC analog output		√
Max/Min hold		√
Max/ hold	√	
Zero adjustment	√	√

Sensor	Silicon photodiode and filter	
Measuring range	20(TM-202),200, 2000, 20000, 200000 Lux 20,200, 2000, 20000 Foot-candle	
Accuracy	±3% (Calibrated to standard incandescent lamp 2856K) ±8% (other visible light source TM-201) ±6%(other visible light source TM-202)	
Angle deviation from cosine characteristics	30°	±2%
	60°	±6%
	80°	±25%

DIMENSION

Meter size (LxWxH)	172x55x38mm
Sensor size (LxWxH)	80x55x25
Weight (including battery)	250g