

TM-508A ... Milliohm Meter Battery or AC/DC Adaptor Powered

TM-508A 數位低阻計

DISPLAY

- 3½ digits LCD display with max. Reading of 2000 .
- Low battery indication.

可用來測量電阻，馬達線圈，變壓器，印刷線路板

3 1/2 LCD 顯示器，最大讀值 1999



FUNCTIONS

- Zero adjustment: External zero adjust knob.
- Very low impedance measurement by four wire type one pair coated clip.
- Wide measurement range, 0.1m to 20K Ohm in 6 positions.
- Function keys: D-H switch lockup readings for LCD display.
- Fuse specification: 2A/250V, 5ø x 20mm, fast Min. Interrupt ratings 1500A.

SPECIFICATIONS:

Range (Ohm)	Accuracy	Resolution (Ohm)	Testing Current	Open-terminal Voltage
200m	±/(0.3%+1d)	0.1m	100mA	1.0 Vmax
2		1m	10mA	
20		10m	10mA	
200		0.1	1mA	
2k		1	1mA	
20k		10	100uA	

▶ 3-1/2 位數，最大顯示 2000

▶ 歸零調整/資料鎖定

▶ 絕緣測試範圍：200mΩ、2Ω、20Ω、200Ω、2kΩ、20KΩ

▶ 精確度：(0.3%+1)

▶ 尺寸：160*100*52 公厘 (長*寬*高)

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)