

UT-612

LCR 錶 最大 19999 位數 電感電容電阻表

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



UT612 是一款性能穩定、安全可靠的掌上型 4 1/2 位元自動量程 LCR 數位電橋表。是測量電感、電容、電阻的專業儀錶，具有功耗低、測量精度高、速度快等特點。串並測量模式選擇，測量元器件品質因數、損耗、相位角、等效電阻測量和直流電阻測量，電感、電容、電阻交流模式下其能夠提供五種測量頻率 (100Hz/120Hz/1KHz/10KHz/100KHz)，更能滿足實際需要。能與 PC 機進行通信，傳送測量資料，並通過專用軟體保存和列印資料和趨勢圖。適用於實驗室、生產線、維修點和教學等多方面的電感、電容、電阻的測量和篩選，是廣大用戶維修用的理想工具。

UNI-T UT-612 100 kHz Handheld LCR Meter

Item	Range	Accuracy
L (H)	20uH/200uH/20mH/200mH/2000mH/20H/200H2000H/20KH	±(0.5%+5)
C (F)	200pF/2nF/20nF/200nF/2000nF/20uF/200uF/2000uF/20mF	±(0.5%+5)
R (Ω)	20 Ω/200 Ω/2K Ω/20K Ω/200K Ω/2M Ω/20M Ω/200M Ω	±(0.3%+5)
Measuring Frequency	100Hz/120Hz/1KHz/10KHz/100KHz	Yes
Measuring Voltage	0.6Vrms	Yes
Measuring Parameters	L/C/R/DCR/Q/D/θ/ESR	Yes
Special Function		
Max. display		19999
D/Q Max. display		1999
D/Q Resolution	0.001	Yes
Automatic Range	Yes	
Real time display for measuring frequency	Yes	
Measurement Models	series and parallel	Yes
Power off automatically	Yes	
Low voltage display	≤6.8V	Yes
Data hold	Yes	
Relative measurement	Yes	
USB Data transmission	Yes	
USB Port /PC Data recording		60000
LCD backlight	Yes	
Analog bar		26pcs
LCR Auto identification measurement	Yes	

General features:

Power: 9V battery(6F22) or USB power

LCD size: 40 X 63mm

Color: Red + Grey

Weigh: 420g

Size: 96 X 193 X 47mm

Accessories: SMD test clip, USB cable, CD software, socket adapter, short-circuit plate

Optional: Kelvin test cable, USB power adapter

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)