

VC60E+

勝利牌_絕緣電阻測試器

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



VICTOR VC60B+/VC60D+/VC60E+

Product Features / 产品特点

新一代电工测试仪表，美观实用款式新潮

功能全，准确度高，操作方便可靠

防尘防潮结构，更适合野外使用

测量各种电力系统、电气设备、防雷设备的绝缘电阻值

可测量交流电压

PRODUCT PARAMETERS

产品参数

STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY



基本功能	量 程	基本精度		
		VC60B ⁺	VC60D ⁺	VC60E ⁺
输出电压	1000V/2500V		±10%	
	2500V/5000V			±10%
测试电流	250V/500V/1000V	±10%		
	250V (R=250KΩ) 1mA	±10%		
	500V (R=500KΩ) 1mA			
	1000V (R=1MΩ) 1mA			
短路电流	<4mA		✓	✓
	<1.8mA	✓		
绝缘电阻	200MΩ: 6.0-199.9MΩ		±(5%±5字)	
1000V	2GΩ: 0.06-1.999GΩ		±(5%±5字)	
	20GΩ: 0.6-19.99GΩ		±(5%±5字)	
绝缘电阻	200MΩ: 5.0-199.9MΩ		±(5%±5字)	
2500V	2GΩ: 0.05-1.999GΩ		±(5%±5字)	±(5%±5字)
	20GΩ: 0.5-19.99GΩ		±(5%±5字)	±(5%±5字)
	200GΩ: 5.0-199.9GΩ			±(10%±5字)
绝缘电阻	2GΩ: 0.05-1.999GΩ			±(5%±5字)
5000V	20GΩ: 0.5-19.99GΩ			±(5%±5字)
	200GΩ: 5.0-199.9GΩ			±(10%±5字)
RANGE	250V: 0.1MΩ-20MΩ	±(4%读数±2字)		
绝缘电阻	500V: 0.1MΩ-50MΩ			
	1000V: 0.1MΩ-100MΩ			
	250V: 20MΩ-500MΩ	±(4%读数±2字)		
	500V: 50MΩ-1000MΩ			
	1000V: 100MΩ-2000MΩ			
电压测量	AC750V	±(1%+6字)	±(1%+6字)	±(1%+6字)
插孔位置	绝缘电阻: L、E AC750V: ACV G			



PRODUCT DISPLAY

产品展示

STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY
STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY



PACKAGING AND ACCESSORIES

产品包装与配件

STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY STRONGER SIGNALS MORE CLEARLY

电阻测试仪



背带



鳄鱼夹



彩盒



说明书



合格证



测试线



电池

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)