


304 不銹鋼吊環螺母



产品信息

product information



产品材质

304不锈钢

规格

M3-M36

型号	点击进入	外径 a	粗度 b	内径 c	底座 d	总高 e	100只重量
	链接	mm	mm	mm	mm	mm	KG
M3	G0	13.44	2.94	7.28	6.94	13.84	0.24
M4	G0	19.14	4.10	10.62	8.42	19.02	0.58
M5	G0	23.10	4.72	13.40	11.10	23.30	0.97
M6	G0	27.26	5.50	16.04	15.12	29.54	1.89
M8	G0	35.04	7.40	20.06	17.86	36.46	3.76
M10	G0	43.80	9.02	25.58	22.00	45.86	6.84
M12	G0	51.02	10.46	29.96	25.80	51.90	10.67
M14	G0	52.34	11.08	30.16	27.22	53.20	11.99
M16	G0	60.04	12.52	34.96	30.32	61.60	17.39
M18	G0	65.74	14.02	37.60	34.84	66.02	24.51
M20	G0	70.04	14.38	41.14	37.46	71.16	28.05
M24	G0	79.66	18.30	43.40	42.44	78.50	47.68
M27	G0	84.50	21.30	42.76	46.70	81.40	67.40
M30	G0	103.20	24.60	54.50	53.10	104.02	102.50
M36	G0	123.80	26.90	67.40	72.90	122.90	187.30

细节展示

show details



优质钢材

Delicate wheels

选用优质304不锈钢线材浇铸而成，用料厚实，承重力大

螺纹深邃

Deep thread

螺纹精准、深邃，拧紧密实
旋转不会发生打滑现象，杜绝使用中安全隐患



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

