

QLK Adjustable, Ratchet Torque Wrenches

Freely set torque values within the capacity range. Replaceable socket, ratchet wrenches.



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

FEATURES

- The ratchet improves efficiency. These wrenches are well suited for repetitive work.
- By replacing the sockets, various sizes of fasteners can be tightened within the tool's capacity range.
- By reversing the ratchet, the wrench can be used to loosen fasteners counter-clockwise.
- Tightening to a torque setting can only be done clockwise.
- Accuracy: $\pm 3\%$ of indicated value over the full range

SPECIFICATIONS

Model QLK(kgf·cm/kgf·m)

Model	Range	Increment	Total length
30QLK	10~30 kgf·cm	0.5 kgf·cm	186 mm
60QLK	20~60 kgf·cm	1 kgf·cm	186 mm
120QLK	40~120 kgf·cm	2 kgf·cm	186 mm
230QLK	70~230 kgf·cm	2 kgf·cm	231.5 mm
250QLK	50~250 kgf·cm	2 kgf·cm	240 mm
450QLK	100~450 kgf·cm	5 kgf·cm	253.5 mm
500QLK	100~500 kgf·cm	5 kgf·cm	253.5 mm
900QLK	200~900 kgf·cm	10 kgf·cm	352 mm
1000QLK	200~1000 kgf·cm	10 kgf·cm	352 mm

Model	Range	Incremen	Total length
1400QLK	400~1400 kgf·cm	10 kgf·cm	392 mm
1800QLK	400~1800 kgf·cm	20 kgf·cm	478 mm
2000QLK	400~2000 kgf·cm	20 kgf·cm	478 mm
2800QLK	4~28 kgf·m	0.2 kgf·m	678 mm
4200QLK	6~42 kgf·m	0.2 kgf·m	950 mm
5600QLK	8~56 kgf·m	0.3 kgf·m	1195 mm
7000QLK	10~70 kgf·m	0.5 kgf·m	1315 mm
8500QLK	10~85 kgf·m	0.5 kgf·m	1388 mm
10000QLK	10~100 kgf·m	0.5 kgf·m	1538 mm
14000QLK	20~140 kgf·m	1 kgf·m	1844 mm
15000QLK	20~150 kgf·m	1 kgf·m	1844 mm
21000QLK	70~210 kgf·m	1 kgf·m	2064 mm

Model N-QLK(cN·m/N·m)

Model	Range	Increment	Total length
N30QLK	100~300 cN·m	5 cN·m	186 mm
N60QLK	2~6 N·m	0.1 N·m	186 mm
N120QLK	4~12 N·m	0.2 N·m	186 mm
N230QLK	7~23 N·m	0.2 N·m	231.5 mm
N250QLK	5~25 N·m	0.2 N·m	240 mm
N450QLK	10~45 N·m	0.5 N·m	253.5 mm
N500QLK	10~50 N·m	0.5 N·m	253.5 mm
N900QLK	20~90 N·m	1 N·m	352 mm
N1000QLK	20~100 N·m	1 N·m	352 mm
N1400QLK	40~140 N·m	1 N·m	392 mm
N1800QLK	40~180 N·m	2 N·m	478 mm
N2000QLK	40~200 N·m	2 N·m	478 mm
N2800QLK	40~280 N·m	2 N·m	678 mm

Model	Range	Increment	Total length
N4200QLK	60~420 N·m	2 N·m	950 mm
N5600QLK	80~560 N·m	3 N·m	1195 mm
N7000QLK	100~700 N·m	5 N·m	1315 mm
N8500QLK	100~850 N·m	5 N·m	1388 mm
N10000QLK	100~1000 N·m	5 N·m	1538 mm
N14000QLK	200~1400 N·m	10 N·m	1844 mm
N15000QLK	200~1500 N·m	10 N·m	1844 mm
N21000QLK	700~2100 N·m	10 N·m	2064 mm

Model PI-QLK(lbf·in)

Model	Range	Increment	Total length
PI120QLK	40~120 lbf·in	2 lbf·in	186 mm
PI230QLK	70~230 lbf·in	2 lbf·in	231.5 mm
PI450QLK	100~450 lbf·in	5 lbf·in	253.5 mm
PI1000QLK	200~1000 lbf·in	10 lbf·in	352 mm
PI2000QLK	400~2000 lbf·in	20 lbf·in	478 mm