

# 306A Click wrenches with removable ratchet

▷ ISO 6789, DIN EN ISO 6789, NF EN ISO 6789.

- Accuracy ex works : +/- 2 % except :
  - R.306-25D, K.315DA, K.325DA : +/- 4 %.
  - R.304DA : +/- 6 %.
- Reliability of mechanism : 50,000 cycles (wrenches to 200 Nm).
- For use with 9x12, 14x18 and Ø 30 mm.
- One-way wrench convertible to two-way by inverting accessories.
- Numbered and supplied with an ISO 6789 calibration certificate.
- Set supplied in a plastic box with ratchet pivot handle (except R.306A25, R.301A).



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

☞	Capacity N.m	End fitting	Graduation N.m	Set contents			Dimensions wrench only		Dimensions including case		
				Wrench	Ratchet	Pivot knob	L (mm)	ΔΔ(kg)	Case	L (mm)	ΔΔ(kg)
<b>R.301A</b>	1-5	9 x 12	0,05	R.304DA	R.372	-	185	0,290	BP.102	205	0,58
<b>R.306A25</b>	5 - 25	9 x 12	0,10	R.306-25D	R.372	-	271	0,45	BP.D1	352	0,98
<b>J.306A50</b>	10 - 50	9 x 12	1,00	J.306-50D	J.372	S.305P	357	0,93	BP.D2	572	1,73
<b>J.306A100</b>	20 - 100	9 x 12	1,00	S.306-100D	J.372	S.305P	437	1,05	BP.D2	572	1,94
<b>S.306A100</b>	20 - 100	9 x 12	1,00	S.306-100D	S.372	S.305P	437	1,05	BP.D2	572	1,95
<b>S.306A200</b>	40 - 200	14 x 18	1,00	S.306-200D	S.382	S.305P	515	1,26	BP.D3	807	2,53
<b>S.306A350</b>	70 - 350	14 x 18	2,00	S.306-350D	S.382	S.305P	725	1,79	BP.D3	807	3,06
<b>K.312A</b>	120-600	14 x 18	2,00	K.315DA	K.382	-	990	5,160	BP.D600	1233	8,80
<b>K.322</b>	200-1000	Ø 30	4,00	K.325D	K.151A	-	1280	5,9	BP.D1000	1418	13,50