


QL-MH

Adjustable Torque Wrench with Metal Handle



- Knurled metal handle version of small and mid range QL.
- Ideal for Oily Working Conditions

Complimentary Products



NOTE3-G
Digital Torque
Wrench Tester



QL
Adjustable Torque
Wrench



QSP
Preset Torque
Wrench



LC3-G
Line Checker



Select proper model according to unit of measure :

Accuracy ±3%

MODEL			TORQUE RANGE						Dimensions [mm]								SQ. DR.		WEIGHT	Optional Carrying Case		
			MIN.~MAX.			GRADUATION																
S.I.	Metric	American	S.I.	Metric	American	S.I.	Metric	American	L	L'	R	h	m	n	d	D	a	b	kg			
			N.m	kgf.cm.	lbf.in.	N.m	kgf.cm.	lbf.in.														
QL2N-MH	20QL-MH	QL15I-2A-MH	0.4-2	4-20	3-15	0.02	0.2	0.1	100	160	11.5	17.5	19	9.2	15	25.5	6.35	11	0.16			
QL5N-MH	50QL-MH	QL30I-2A-MH	1-5	10-50	6-30	0.05	0.5	0.2	135	195									0.19			
QL10N-MH	100QL-MH	QL50I-2A-MH	2-10	20-100	10-50	0.1	1	0.5	162	230	13	22	19	9.2	15	25.5	6.35	11	0.25			
QL15N-MH	150QL-MH	QL100I-2A-MH	3-15	30-150	20-100	0.1	1	1											180	260	16	25.6
QL25N-MH	225QL-MH	Upon Request	5-25	50-250		0.25	2.5		255	340	17	32	28.0	12.2	21.7	37	12.7	15.4	0.69			
QL50N-MH	450QL-MH		10-50	100-500		0.5	5		320	400	18.8	33.5							0.79			
QL100N-MH	900QL4-MH		20-100	200-1000		1	10		400	495	20	38.4							1.4			
QL140N-MH	1400QL-MH		30-140	300-1400					2	20	600	695								22.5	44.5	1.9
QL200N-MH	1800QL4-MH		40-200	400-2000							kgf.m. 4-28	kg.m 0.2								27.2	46.5	
QL280N-MH	2800QL4-MH	40-280																				

NOTE

Also see QL which is the standard model series that features a resin grip.



Carrying Case 842 / 843



Carrying Case 846 / 847

Dimensions

