



30-440-2



Digital Caliper

Digital Reading 0.001" / 0,1 mm

- Ultra light weight (1.7 oz.) for easy handling.
- Inside, outside, depth and step measuring. Range 6"/150 mm.
- Super Polyimid, 60% fiberglass reinforced plastic of highest quality. Depth rod, frame and housing are made of non-conductive plastic. Resistant to chemicals and corrosion.
- Large, high contrast LCD display.
- Zero setting at any position within entire range. Direct inch/mm conversion.
- Alarm signal for low battery and over speed. 2 year battery life (approx.).
- Jaw Length: 1.57"/40 mm. Resolution: 0.001"/0,1 mm Accuracy: 0.004"/0.1 mm.
- Furnished in fitted case.

Description	Part No.
Digital Caliper	30-440-2
Repl. Battery	07-310-6



12-533-6

6" Fractional Caliper

- Decimal inch, metric and fractional display.
- Measuring range: 0 - 6"/0 - 150 mm
- Resolution: 0.0005"/0.01 mm/1/128"
- Accuracy: ±0.001"/0.03 mm
- Jaw length: 1 19/32"
- Includes thumb wheel.
- Origin position retained through on/off cycle.
- Certificate of calibration traceable to NIST included.
- Furnished in fitted case.

Description	Part No.
6" Fractional Caliper	12-533-6
Repl. Battery	07-310-6



14-792-6

6" Electronic Caliper with 5/8" Easy to Read LCD Display.

- Precision ground stainless steel construction.
- Inch-Metric conversion.
- Zero set anywhere in range.
- Auto power on/off.
- With thumb roller and slide lock.
- Jaw length: 1 19/32"
- Display Resolution: 0.0005"/0.01 mm
- Accuracy: ±0.001"/0.03 mm
- Furnished in fitted case.

Description	Part No.
6" LCD Caliper	14-792-6
Repl. Battery	07-310-6



6", 8" & 12" Models

24" & 40" Models

Electronic Caliper Series

From 6" to 40" with Certificate Traceable to NIST.

- Precision ground stainless steel construction.
- 6, 8, and 12" models with thumb roll measure outside, inside, step and depth dimensions.
- 24 and 40" models with fine adjustment, preset value 0.7874"/20 mm for inside measuring.
- Inch-Metric conversion.
- Absolute or Incremental position switching.
- Zero set anywhere within range.
- Auto power on/off.
- Display Resolution: 0.0005"/0.01 mm
- Furnished in fitted case.



Range	Jaw Thickness	Jaw Length	Accuracy	Part No.
0 - 6"/0 - 150 mm	0.125"	1.56"	±0.001"/0.025 mm	13-610-1
0 - 8"/0 - 200 mm	0.142"	1.56"	±0.001"/0.025 mm	13-611-9
0 - 12"/0 - 300 mm	0.150"	2.56"	±0.0016"/0.041 mm	13-612-7
0 - 24"/0 - 600 mm	0.218"	3.93"	±0.002"/0.051 mm	13-613-5
0 - 40"/0 - 1000 mm	0.312"	5.90"	±0.003"/0.076 mm	13-614-3
Repl. Battery				07-310-6