

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>

戶外防水接线盒 IP68防水

PC阻燃 可埋地下



安全阻燃



CE认证



密封防尘



密封防水



品质耐用

产品·参数

PRODUCT PARAMETERS

- 【产品名称】：防水接线盒
- 【阻燃等级】：PC
- 【产品等级】：IP68
- 【螺丝材质】：304不锈钢螺丝
- 【盒体材质】：V-1
- 【密封件】：硅胶圈
- 【用途】：户外灯/地埋灯防水接线电路板保护盒



尺寸 总汇表

SUMMARY OF DIMENSIONS

产品 型号	箱体尺寸 (mm)	防水 等级	接线 孔 数量	可装 防水头
L1	70*40*40	IP68	0-4孔	FG7/PG9/PG13.5
L2	90*50*40	IP68	0-6孔	FG7/PG9/PG13.5
L3	120*70*48	IP68	0-6孔	FG7/PG9/PG13.5
L4	140*85*56	IP68	0-8孔	FG9/PG13.5/M25
注：手工测量尺寸数据允许0.3-0.5mm的差距				



M25

通线范围
12-15MM



PG13.5

通线范围
7-12MM



PG9

通线范围
4-8MM



PG7

通线范围
3-6.5MM

电缆外径参考图

CABLE DIAMETER REFERENCE DRAWING

2芯 (国标参数)	3芯 (国标参数)	4芯 (国标参数)
2*0.75—线芯外径6.1mm	3*0.75—线芯外径6.5mm	4*0.5 —线芯外径6.0mm
2*1.0 —线芯外径6.6mm	3*1.0 —线芯外径7.0mm	4*0.75—线芯外径7.1mm
2*1.5 —线芯外径7.6mm	3*1.5 —线芯外径8.1mm	4*1.0 —线芯外径7.8mm
2*2.5 —线芯外径9.0mm	3*2.5 —线芯外径9.6mm	4*1.5 —线芯外径9.2mm
2*4.0—线芯外径10.5mm	3*4.0—线芯外径11.2mm	4*2.5 —线芯外径10.8mm
2*6.0—线芯外径12.2mm	3*6.0—线芯外径13.2mm	

应用·场景

APPLICATION SCENARIOS

主要用于户外防水设备 路灯/地埋灯/庭院灯/户外投光灯等

